

AM0036

Large-scale Methodology

Fuel switch from fossil fuels to biomass in heat generation equipment

Version 05.0

Sectoral scope(s): 01 and 04



United Nations
Framework Convention on
Climate Change

TABLE OF CONTENTS	Page
1. INTRODUCTION	4
2. SCOPE, APPLICABILITY, AND ENTRY INTO FORCE	4
2.1. Scope	4
2.2. Applicability	4
2.3. Entry into force	6
2.4. Applicability of sectoral scopes	6
3. NORMATIVE REFERENCES	6
3.1. Selected approach from paragraph 48 of the CDM modalities and procedures	7
4. DEFINITIONS	7
5. BASELINE METHODOLOGY	8
5.1. Project boundary	8
5.2. Project documentation	10
5.3. Identification of the baseline scenario and demonstration of additionality	10
5.3.1. Identification of alternative scenarios.....	10
5.4. Baseline emissions.....	12
5.4.1. Baseline emissions from fossil fuel combustion for heat generation ($BE_{HG,y}$)	12
5.4.2. Baseline emissions due to uncontrolled burning or decay of the biomass residues	16
5.5. Project emissions	19
5.5.1. Emissions from on-site fossil fuel combustion ($PE_{FF,y}$).....	20
5.5.2. Emissions from on-site electricity consumption ($PE_{EC,y}$)	20
5.5.3. Emissions from transportation of biomass to the project site ($PE_{TR,y}$)	21
5.5.4. Emissions from combustion of biomass residues in the heat generation equipment ($PE_{BF,y}$).....	21
5.5.5. Emissions from wastewater generated from the treatment of biomass ($PE_{WW,y}$)	22
5.5.6. Emissions from the production of biogas in year y ($PE_{BG,y}$)	23

5.5.7.	Emissions associated with the cultivation of land to produce biomass in year y ($PE_{BC,y}$).....	23
5.6.	Leakage.....	23
5.7.	Emission reductions	23
5.8.	Changes required for methodology implementation in 2 nd and 3 rd crediting periods.....	24
5.9.	Data and parameters not monitored	24
6.	MONITORING METHODOLOGY	26
6.1.	Data and parameters monitored	27

1. Introduction

1. The following table describes the key elements of the methodology:

Table 1. Methodology key elements

Typical project(s)	Fuel switch from fossil fuels to biomass in the generation of heat. Applicable activities are retrofit or replacement of existing heat generation equipment and installation of new heat generation equipment
Type of GHG emissions mitigation action	Renewable energy: Displacement of more-GHG-intensive heat generation using fossil fuel and avoidance of CH ₄ emissions from anaerobic decay of biomass residues

2. Scope, applicability, and entry into force

2.1. Scope

2. This methodology is applicable to project activities that operate biomass (co-)fired heat generation equipment. The CDM project activity may include the following activities or, where applicable, combinations of these activities:
- (a) The installation of new plants at a site where currently no heat generation occurs (Greenfield projects);
 - (b) The installation of new plants at a site where currently heat generation occurs. The new plant replaces or is operated next to existing plants (capacity expansion projects);
 - (c) The improvement of energy efficiency of existing plants (energy efficiency improvement projects), which can also lead to a capacity expansion, e.g. by retrofitting the existing plant;
 - (d) The total or partial replacement of fossil fuels by biomass in existing plants or in new plants that would have been built in the absence of the project (fuel switch projects), e.g. by increasing the share of biomass use as compared to the baseline, or by retrofitting an existing plant to use biomass.

2.2. Applicability

3. The methodology is applicable under the following conditions:
- (a) The heat generated in the heat generation equipment is either not used for power generation or, if power is generated using the heat generated by the heat generation equipment, it is not increased as a result of the project activity, i.e.:
 - (i) The power generation capacity installed remains unchanged due to the implementation of the project activity and is maintained at the pre-project level throughout the crediting period; and

- (ii) The annual power generation during the crediting period is not more than 10% larger than the highest annual power generation in the most recent three years prior to the implementation of the project activity;
 - (b) The use of biomass residues or increasing the use of biomass residues beyond historical levels is technically not possible at the project site without a significant capital investment in:
 - (i) Either the retrofit or replacement of existing heat generation equipment or the installation of new heat generation equipment; or
 - (ii) Establishing a new dedicated biomass supply chain for the purpose of the project activity (e.g. collecting and cleaning contaminated new sources of biomass residues that could otherwise not be used for energy purposes);
 - (c) Biomass types used by the project activity are limited to biomass residues, biogas, Refuse Derived Fuel (RDF) and/or biomass from dedicated plantations. Refuse Plastic Fuel (RPF) can also be co-fired in the equipment, but for the purpose of this methodology RDF and RPF shall be considered as fossil fuels;¹
 - (d) Fossil fuels may be co-fired in the project plant. However, the amount of fossil fuels co-fired does not exceed 50% of the total fuel fired on an energy basis;
 - (e) The biomass used by the project facility is not processed chemically or biologically (e.g. through esterification, fermentation, hydrolysis, pyrolysis, bio- or chemical-degradation, etc.) prior to combustion. Thermal degradation, drying and mechanical processing, such as shredding and pelletisation, are allowed;
 - (f) The biomass used at the project site, i.e. the site where the project activity is implemented, are not be stored for more than one year;
4. For projects that use biomass residues from a production process (e.g. production of sugar or wood panel boards), the implementation of the project does not result in an increase of the processing capacity of raw input (e.g. sugar, rice, logs, etc.) or in other substantial changes (e.g. product change) in this process.
 5. In the case biomass from dedicated plantations is used, the applicability conditions of "TOOL16: Project and leakage emissions from biomass" apply.
 6. If biogas is used, it must be generated by anaerobic digestion of wastewater, and:
 - (a) If the wastewater generation source is registered as a CDM project activity, the details of the wastewater project shall be included in the PDD, and emission reductions from biogas energy generation are claimed using this methodology;
 - (b) If the wastewater source is not a CDM project, the amount of biogas does not exceed 50% of the total fuel fired on energy basis.
 7. In case of project activities that involve the replacement or retrofit of existing heat generation equipment, emission reductions may only be accounted until the time when the existing equipment would have reached the end of its technical time in the crediting

¹ If the project participants want to claim emission reduction for the biodegradable component in RPF, a revision to this methodology shall be required.

period, i.e. after the point in time when the existing equipment would have to be replaced due to the expiry of its technical lifetime in the baseline scenario, emission reductions cannot be accounted. For the purpose of demonstrating this applicability condition, project participants should determine and document the remaining lifetime of each unit of the existing heat generation equipment in accordance with “TOOL10: Tool to determine the remaining lifetime of equipment”. In the case of several existing units with a different remaining lifetime, the shortest lifetime among the units should be used to determine the point in time until which CERs can be claimed.

8. In addition, the applicability conditions of the methodological tools referred below shall apply.

2.3. Entry into force

9. The date of entry into force is the date of the publication of the EB 100 meeting report on 31 August 2018.

2.4. Applicability of sectoral scopes

10. For validation and verification of CDM projects and programme of activities by a designated operational entity (DOE) using this methodology, application of sectoral scopes 01 and 04 is mandatory.

3. Normative references

11. This baseline and monitoring methodology is based on elements from the following approved baseline and monitoring methodologies:
 - (a) “ACM0014: Treatment of wastewater”;
 - (b) “AMS-III.H.: Methane recovery in wastewater treatment”.
12. This methodology also refers to the latest approved versions of the following tools:
 - (a) “TOOL02: Combined tool to identify the baseline scenario and demonstrate additionality”;
 - (b) “TOOL03: Tool to calculate project or leakage CO₂ emissions from fossil fuel combustion”;
 - (c) “TOOL04: Emissions from solid waste disposal sites”;
 - (d) “TOOL07: Tool to calculate the emission factor for an electricity system”;
 - (e) “TOOL09: Determining the baseline efficiency of thermal or electric energy generation systems”;
 - (f) “TOOL10: Tool to determine the remaining lifetime of equipment”;
 - (g) “TOOL11: Assessment of the validity of the original/current baseline and update of the baseline at the renewal of a crediting period”;
 - (h) “TOOL12: Project and leakage emissions from transportation of freight”;
 - (i) “TOOL16: Project and leakage emissions from biomass”.

13. For more information regarding the proposed new methodologies and the tools as well as their consideration by the Executive Board please refer to [<http://cdm.unfccc.int/goto/MPappmeth>](http://cdm.unfccc.int/goto/MPappmeth).

3.1. Selected approach from paragraph 48 of the CDM modalities and procedures

14. “Emissions from a technology that represents an economically attractive course of action, taking into account barriers to investment”.

4. Definitions

15. The definitions contained in the Glossary of CDM terms shall apply.

16. The following definitions apply for this methodology:

- (a) **Biomass** non-fossilized and biodegradable organic material originating from plants, animals and microorganisms including:
 - (i) Biomass residue;
 - (ii) The non-fossilized and biodegradable organic fractions of industrial and municipal wastes; and
 - (iii) The gases and liquids recovered from the decomposition of non-fossilized and biodegradable organic material;
- (b) **Biomass residues** - non-fossilized and biodegradable organic material originating from plants, animals and micro-organisms which is a by-product, residue or waste stream from agriculture, forestry and related industries;
- (c) **Heat** - is useful thermal energy that is generated in heat generation equipment and transferred to a heat carrier (e.g. hot liquids, hot gases,² steam, etc.) for utilization in thermal applications and processes. For the purposes of this methodology, heat does not include waste heat, i.e. heat that is transferred to the environment without utilization, for example, heat in flue gas, heat transferred to cooling towers or any other heat losses. Note that heat refers to the *net* quantity of thermal energy that is transferred to a heat carrier at the heat generation equipment. For example, in case of a boiler it refers to the difference of the enthalpy of the steam generated in the boiler and the enthalpy of the feed water and, if applicable, any condensate return;
- (d) **Heat generation equipment** - is a facility that generates heat by combustion of fuels and supplies heat to thermal applications or processes. This includes, for example, a boiler that supplies steam or hot water, a heater that supplies hot oil or thermal fluid, or a furnace that supplies hot gas or combustion gases. When several heat generation equipment's are included in one project activity, each heat generation equipment is referred to as “unit”;
- (e) **Efficiency of heat generation** - is the quantity of heat generated per unit quantity of fuel fired (both expressed in terms of energy using the same units). The average

² Hot gases may include combustion gases from a furnace if the gases are used as heat carrier, without further combustion.

net efficiency of heat generation refers to the efficiency of heat generation over a longer time interval (e.g. one year) that is representative for different loads and operation modes, including start-ups. When considering more than one unit, the average efficiency of heat generation corresponds respectively to the heat generated by all units divided by the quantity of fuel fired in the same units (based on Net Calorific Values).

5. Baseline methodology

5.1. Project boundary

17. The spatial extent of the project boundary encompasses:

- (a) The heat generation equipment and related equipment at the project site;
- (b) If applicable, all off-site heat sources that supply heat to the site where the CDM project activity is located (either directly or via a district heating system);
- (c) The means for transportation of biomass to the project site (e.g. vehicles);
- (d) The site where the biomass residues would have been left for decay under anaerobic conditions. This is applicable only to cases where the biomass residues would in the absence of the project activity be dumped under anaerobic conditions;
- (e) If the feedstock is biomass sourced from dedicated plantations, the geographic boundaries of the dedicated plantations;
- (f) If biogas is included, the site of the anaerobic digester.

Table 2. Emission sources included in or excluded from the project boundary

Source		Gas	Included	Justification/Explanation
Baseline	Fossil fuel combustion for heat generation	CO ₂	Yes	Important emission source
		CH ₄	No	Excluded for simplification. This is conservative
		N ₂ O	No	Excluded for simplification. This is conservative
	Uncontrolled burning or decay of the biomass residues	CO ₂	No	It is assumed that CO ₂ emissions from surplus biomass residues do not lead to changes of carbon pools in the LULUCF sector
		CH ₄	Yes or No	Project participants may decide to include this emission source, where cases B1, B2 or B3 as described in "TOOL16: Project and leakage emissions from biomass" are identified as the most likely baseline scenario for the use of the biomass residues
		N ₂ O	No	Excluded for simplification. This is conservative

Source		Gas	Included	Justification/Explanation
Project activity	On-site fossil fuel and electricity consumption	CO ₂	Yes	Important emission source
		CH ₄	No	Excluded for simplification. This emission source is assumed to be very small
		N ₂ O	No	Excluded for simplification. This emission source is assumed to be very small
	Off-site transportation of biomass	CO ₂	Yes	Important emission source.
		CH ₄	No	Excluded for simplification. This emission source is assumed to be very small
		N ₂ O	No	Excluded for simplification. This emission source is assumed to be very small
	Combustion of biomass for heat generation	CO ₂	No	It is assumed that CO ₂ emissions from surplus biomass do not lead to changes of carbon pools in the LULUCF sector
		CH ₄	Yes or No	This emission source must be included if project participants include CH ₄ emissions from uncontrolled burning or decay of the biomass residues in the baseline scenario
		N ₂ O	No	Excluded for simplification. This emission source is assumed to be small
	Wastewater from the treatment of biomass	CO ₂	No	It is assumed that CO ₂ emissions from surplus biomass do not lead to changes of carbon pools in the LULUCF sector
		CH ₄	Yes	This emission source shall be included in cases where the waste water is treated (partly) under anaerobic conditions
		N ₂ O	No	Excluded for simplification. This emission source is assumed to be small
	Cultivation of land to produce biomass feedstock	CO ₂	Yes	This emission source shall be included in cases biomass from dedicated plantation is used
		CH ₄	Yes	This emission source shall be included in cases biomass from dedicated plantation is used
		N ₂ O	Yes	This emission source shall be included in cases biomass from dedicated plantation is used

5.2. Project documentation

18. The project participants shall document the specific situation of the CDM project activity in the CDM-PDD, at least for the following:
- (a) For each plant generating heat that operated at the project site in the three years prior to the start of the CDM project activity: the type and capacity of the heat generators, the types and quantities of fuels which were used in the heat generators, the type and capacity of heat engines, and whether the equipment continues operation after the start of the CDM project activity;
 - (b) For each plant generating heat installed under the CDM project activity: the type and capacity of the heat generators, the types and quantities of fuels used in the heat generators, the type and capacity of heat engines and direct heat extractions;
 - (c) For each plant generating heat that would be installed in the absence of the CDM project activity: the type and capacity of the plant, the type and capacity of the heat generators, and the types and quantities of fuels which would be used in each heat generator;
 - (d) The average amounts of heat that would be imported from off-site sources in the absence of the CDM project activity and the import forecast for the project scenario.

5.3. Identification of the baseline scenario and demonstration of additionality

19. The selection of the baseline scenario and demonstration of additionality should be conducted by applying the "TOOL02: Combined tool to identify the baseline scenario and demonstrate additionality"

5.3.1. Identification of alternative scenarios

20. Realistic and credible alternatives should be separately determined for the following two components of the project activity:
- (a) Heat generation in the absence of the project activity;
 - (b) What would happen to the biomass in the absence of the project activity.
21. The alternatives to be analyzed for **heat generation** may include, *inter alia*:
- (a) H1: The proposed project activity not undertaken as a CDM project activity (heat generation with biomass);
 - (b) H2: Continued operation of the existing heat generation equipment using the same fuel mix or less biomass as in the past;
 - (c) H3: Continued operation of the existing unit(s) using a different fuel (mix);
 - (d) H4: Improvement of the performance of the existing heat generation equipment;
 - (e) H5: Continued operation of the existing unit(s) using the same fuel mix or less biomass as in the past AND installation of new heat generation equipment that is/are fired with the same fuel type(s) and the same fuel mix (or a lower share of biomass) as the existing equipment;

- (f) H6: Replacement of the existing heat generation equipment with new heat generation equipment.
22. When using biomass residues, the alternative scenarios of the biomass residues in absence of the project activity shall be determined following the guidance in “TOOL16: Project and leakage emissions from biomass”.
 - (a) In addition to the alternative scenarios provided in “TOOL16: Project and leakage emissions from biomass”, the alternative scenarios shall include scenario B5: The biomass residues are used for power or heat generation at the project site in new and/or existing plants.
 23. If biomass residues have already been used for heat generation at the project site prior to the implementation of the project activity, the most plausible baseline scenario for the use of the biomass residues should only be determined for the additional biomass residues used over and above the historical levels.
 24. Where different types or sources of biomass are used in the project activity, the most plausible baseline scenario for the use of biomass should be determined for each type and source of biomass separately. The respective biomass types, quantities and sources should be documented transparently in the CDM-PDD.
 25. In case the proposed project activity includes the use of biogas, the project shall consider the following baseline alternatives for the biogas:
 - (a) BG1: No biogas would be generated and wastewater would not be treated by anaerobic digestion;
 - (b) BG2: Biogas is captured and flared;
 - (c) BG3: Biogas is captured and used to produce electricity and/or thermal energy;
 - (d) BG4: Biogas is captured and used as feedstock or transportation fuel.
 26. When defining plausible and credible alternative scenarios for the use of biogas, the guidance below should be followed:
 - (a) If scenario BG1 and BG2 are selected, no biogas shall be included in the baseline scenario of the proposed project activity;
 - (b) If scenario BG3 is selected, the same amount of biogas produced in the project shall be included in the baseline scenario. For the purpose of calculating the “Baseline Emissions” the biogas shall be considered a biomass residue;
 - (c) If scenario BG4 is selected, the methodology is not applicable;
 - (d) In case any emission reductions are claimed for the avoidance of methane in scenario BG1, the baseline scenario for and additionality of the biogas shall be determined in a separate biogas CDM project activity using methodology ACM0014 or AMS-III.H. In addition, all baseline, project and emissions not related to energy generation shall be accounted for in the biogas CDM project activity. Any incremental costs related to biogas energy generation in the project scenario shall be included in the biogas CDM PDD (e.g. costs of pipes, burner and control systems) and not in the proposed project activity under this methodology;

27. In case of scenario BG2 and BG3 any incremental costs related to biogas energy generation in the project scenario shall be included in the PDD of the proposed project activity using this methodology. In case the biogas is supplied by an existing CDM project activity its reference shall be included in the PDD. Any required changes to the existing CDM project activity (e.g. change in project emissions due to flare emissions, reduction of CERs due to energy supply to this methodology) shall be dealt with in the PDD of the existing CDM project activity.
28. The alternatives to the project activity shall be in compliance with all applicable legal and regulatory requirements – taking into account EB decisions with respect to national and/or sectoral policies and regulations in determining a baseline scenario³ – even if these laws and regulations have objectives other than GHG reductions, e.g. to mitigate local air pollution. For example, such requirements could include a regulation on energy efficiency or emission standards for heat generation equipment.
29. If an alternative does not comply with all applicable legislation and regulations, then show that, based on an examination of current practice in the country or region in which the law or regulation applies, those applicable legal or regulatory requirements are systematically not enforced and that non-compliance with those requirements is widespread in the country. If this cannot be shown, then eliminate the alternative from further consideration.

5.4. Baseline emissions

30. Baseline emissions include CO₂ emissions from fossil fuel combustion in the heat generation equipment in the absence of the project activity and, if included in the project boundary, CH₄ emissions from the treatment of biomass in the absence of the project activity:

$$BE_y = BE_{HG,y} + BE_{BF,y} \quad \text{Equation (1)}$$

Where:

BE_y	=	Baseline emissions during the year y (tCO ₂ e/yr)
$BE_{HG,y}$	=	Baseline emissions from fossil fuel combustion for heat generation in the heat generation equipment in year y (tCO ₂ /yr)
$BE_{BF,y}$	=	Baseline emissions due to uncontrolled burning or decay of the biomass residues in year y (tCO ₂ e/yr)

5.4.1. Baseline emissions from fossil fuel combustion for heat generation ($BE_{HG,y}$)

31. Baseline emissions from fossil fuel combustion in the heat generation equipment are determined by multiplying the heat generated with fossil fuels that are displaced by biomass with the CO₂ emission factor of the least carbon-intensive fossil fuels that would

³ Annex 3 of the 22nd EB meeting report: “Clarifications on the treatment of national and/or sectoral policies and regulations (paragraph 45(e)) of the CDM Modalities and Procedures) in determining a baseline scenario (version 2)”.

be used in the absence of the project activity and by dividing by the average net efficiency of heat generation in the heat generation equipment, as follows:

$$BE_{HG,y} = \frac{HG_{PJ,biomass,y} \times EF_{FF,CO_2,y}}{\eta_{heat,FF}} \quad \text{Equation (2)}$$

Where:

$BE_{HG,y}$	=	Baseline emissions from fossil fuel combustion for heat generation in the heat generation equipment in year y (tCO ₂ e/yr)
$HG_{PJ,biomass,y}$	=	Heat generated with incremental biomass used as a result of the project activity during the year y (GJ/yr)
$EF_{FF,CO_2,y}$	=	CO ₂ emission factor of the fossil fuel type displaced by biomass for the year y (tCO ₂ e/GJ)
$\eta_{heat,FF}$	=	Average net efficiency of the heat generation equipment if fired with fossil fuels in the baseline (ratio)

5.4.1.1. Determination of $EF_{FF,CO_2,y}$

32. For the purpose of determining $EF_{FF,CO_2,y}$, as a conservative approach, the least carbon intensive fuel type (i.e. the fuel type with the lowest CO₂ emission factor per GJ) should be used among the fossil types used in the heat generation equipment at the project site during the most recent three years prior to the implementation of the project activity and the fossil fuel types used in the heat generation equipment at the project site during the year y .
33. The average net efficiency of the heat generation equipment if fired with fossil fuels in the baseline shall be determined using the latest approved version of "TOOL09: Determining the baseline efficiency of thermal or electric energy generation systems".

5.4.1.2. Determination of $HG_{PJ,biomass,y}$

34. The determination of $HG_{PJ,biomass,y}$ depends on whether only fossil fuels would be used for heat generation in the absence of the project activity (case A) or whether along with fossil fuels some biomass also would be used in the absence of the project activity (case B).
35. The guidance under case A should be followed if:
 - (a) No biomass has been used for heat generation at the project site during the most recent three years prior to the implementation of the project activity; and
 - (b) The most plausible baseline scenario is that heat would continue to be generated only with fossil fuels.
36. The guidance under case B should be followed if:
 - (a) Biomass has already been used in heat generation equipment for heat generation at the project site prior to the implementation of the project activity; and
 - (b) The most plausible baseline scenario is that heat would continue to be generated partly with fossil fuels and partly with biomass.

5.4.1.2.1. Case A: No use of biomass for heat generation in the absence of the project activity

37. In this case, $HG_{PJ,biomass,y}$ corresponds to the *total* quantity of heat generated from firing biomass ($HG_{PJ,biomass,y} = HG_{PJ,biomass,total,y}$).
38. $HG_{PJ,biomass,total,y}$ is determined based on the fraction of biomass that are used for heat generation in the heat generation equipment, taking into account all biomass types k and fossil fuel types i fired in the project heat generation equipment during a year y , as follows:

$$HG_{PJ,biomass,total,y} = HG_{PJ,total,y} \times \frac{\sum_k BF_{k,y} \times NCV_k}{\sum_k BF_{k,y} \times NCV_k + \sum_i FC_{i,y} \times NCV_i} \quad \text{Equation (3)}$$

Where:

$HG_{PJ,biomass,total,y}$	=	Total heat generated from firing biomass in all heat generation equipment at the project site during the year y (GJ/yr)
$HG_{PJ,total,y}$	=	Total heat generated in the heat generation equipment at the project site, using both biomass and fossil fuels, during the year y (GJ/yr)
$BF_{k,y}$	=	Quantity of biomass types k fired in all units of heat generation equipment at the project site during the year y (tons of dry matter or liter) ⁴
NCV_k	=	Net calorific value of the biomass types k (GJ/ton of dry matter or GJ/liter)
$FC_{i,y}$	=	Quantity of fossil fuel types i fired in all heat generation equipment at the project site during the year y (mass or volume unit) ⁵
NCV_i	=	Net calorific value of the fossil fuel types i (GJ/mass or volume unit)

5.4.1.2.2. Case B: Use of some biomass for heat generation in the absence of the project activity

39. In this case, only the use of biomass beyond historical levels should be attributed to the CDM project activity. Hence, $HG_{PJ,biomass,y}$ refers to the additional (i.e. additional to the baseline scenario) quantity of heat generated from the combustion of biomass, as a result of the CDM project activity.
40. As the level of biomass use in the absence of the project activity is associated with significant uncertainty, use, as a conservative approach, for $HG_{PJ,biomass,y}$ the minimum value among the following two options:
- (a) The difference between the total quantity of heat generated from biomass in all heat generation equipment at the project site in the year y ($HG_{PJ,biomass,total,y}$) and

⁴ Use tons of dry matter for solid biomass and for biogas the volume shall be referred to Normal Temperature and Pressure conditions (NTP).

⁵ Use a mass unit for solid fuels and a volume unit for liquid and gaseous fuels.

the highest annual historical heat generation with biomass among the most recent three years prior to the implementation of the project activity, as follows:

$$HG_{PJ,biomass,y} = HG_{PJ,biomass,total,y} - \text{Equation (4)}$$

$$MAX\{HG_{biomass,historic,n}; HG_{biomass,historic,n-1}; HG_{biomass,historic,n-2}\}$$

Where:

- $HG_{PJ,biomass,y}$ = Heat generated with incremental biomass used in the project activity during the year y (GJ/yr)
- $HG_{PJ,biomass,total,y}$ = Total heat generated from firing biomass in all heat generation equipment at the project site during the year y (GJ/yr)
- $HG_{biomass,historic,n}$ = Historical annual heat generation from firing biomass in the heat generation equipment at the project site during the year n (GJ/yr)
- n = Year prior to the implementation of the project activity

- (b) The difference between the total quantity of heat generated from biomass in all heat generation equipment in the year y ($HG_{PJ,biomass,total,y}$) and the total heat generation during the year y ($HG_{PJ,total,y}$) multiplied with the highest historical fraction of heat generation with biomass residues from the most recent three years, as follows:

$$HG_{PJ,biomass,y} \text{Equation (5)}$$

$$= HG_{PJ,biomass,total,y}$$

$$- HG_{PJ,total,y}$$

$$\times MAX\left\{\frac{HG_{biomass,historic,n}}{HG_{total,historic,n}}; \frac{HG_{biomass,historic,n-1}}{HG_{total,historic,n-1}}; \frac{HG_{biomass,historic,n-2}}{HG_{total,historic,n-2}}\right\}$$

Where:

- $HG_{PJ,biomass,y}$ = Heat generated with incremental biomass used as a result of the project activity during the year y (GJ/yr)
- $HG_{PJ,biomass,total,y}$ = Total heat generated from firing biomass in all heat generation equipment at the project site during the year y (GJ/yr)
- $HG_{PJ,total,y}$ = Total heat generated in heat generation equipment at the project site, using both biomass and fossil fuels, during the year y (GJ/yr)
- $HG_{biomass,historic,n}$ = Historical annual heat generation from using biomass in heat generation equipment at the project site during the year n (GJ/yr)
- $HG_{total,historic,n}$ = Historical annual total heat generation, from using biomass and fossil fuels, in heat generation equipment at the project site during the year n (GJ/yr)
- n = Year prior to the implementation of the project activity

41. The historical fraction of heat generation with biomass can be determined based on the quantities of biomass types k and fossil fuel types i used historically in the heat generation equipment operated at the project site, as follows:

$$\frac{HG_{biomass,historic,n}}{HG_{total,historic,n}} = \frac{\sum_k BF_{k,n} \times NCV_k}{\sum_k BF_{k,n} \times NCV_k + \sum_i FC_{i,n} \times NCV_i} \quad \text{Equation (6)}$$

Where:

$HG_{biomass,historic,n}$	=	Historical annual heat generation from using biomass in heat generation equipment at the project site during the year n (GJ/yr)
$HG_{total,historic,n}$	=	Historical annual total heat generation, from using biomass and fossil fuels, in heat generation equipment at the project site during the year n (GJ/yr)
$BF_{k,n}$	=	Quantity of biomass types k used in all heat generation equipment at the project site during the historical year n (tons of dry matter or liter) ⁴
NCV_k	=	Net calorific value of the biomass types k (GJ/ton of dry matter or GJ/liter)
$FC_{i,n}$	=	Quantity of fossil fuel types i fired in all heat generation equipment at the project site during the historical year n (mass or volume unit) ⁵
NCV_i	=	Net calorific value of the fossil fuel types i (GJ/mass or volume unit)
n	=	Year prior to the implementation of the project activity

5.4.2. Baseline emissions due to uncontrolled burning or decay of the biomass residues

42. If included in the project boundary, baseline emissions due to uncontrolled burning or decay of the biomass residues ($BE_{BF,y}$) should be determined consistent with the most plausible baseline scenario for the use of the biomass residues, following the procedures for the respective baseline scenario, as outlined below. Where different baseline scenarios apply to different types or quantities of biomass residues, the procedures as outlined below should be applied respectively to the different quantities and types of biomass residues.
43. For this purpose, determine for each biomass residue types k the quantity of biomass residue used for heat generation as a result of the project activity ($BF_{PJ,k,y}$) as follows:
- If **no biomass** has been used for heat generation at the project site during the most recent three years prior to the implementation of the project activity and if the most plausible baseline scenario is that heat would continue to be generated only with fossil fuels, use $BF_{PJ,k,y} = BF_{k,y}$ for all biomass residue types k ;
 - If only **one type of biomass residue** k has been used for heat generation at the project site prior to the implementation of the project activity and if only this type of biomass residue is used during the year y after implementation of the project activity, use for $BF_{PJ,k,y}$ the product of the quantity of biomass residue types k fired in all heat generation equipment at the project site during the year y ($BF_{k,y}$) and the

fraction of heat generated with biomass residues as a result of the project activity, as follows:

$$BF_{PJ,k,y} = BF_{k,y} \times \frac{HG_{PJ,biomass,y}}{HG_{PJ,biomass,total,y}} \quad \text{Equation (7)}$$

Where:

$BF_{PJ,k,y}$	=	Quantity of biomass residue types k used for heat generation as a result of the project activity during the year y (tons of dry matter or liter) ⁴
$BF_{k,y}$	=	Quantity of biomass residue types k fired in all units of heat generation equipment at the project site during the year y (tons of dry matter or liter) ⁴
$HG_{PJ,biomass,y}$	=	Heat generated with incremental biomass residues used as a result of the project activity during the year y (GJ/yr)
$HG_{PJ,biomass,total,y}$	=	Total heat generated from firing biomass residues in all heat generation equipment at the project site during the year y (GJ/yr)

- (c) In all **other cases** (use of more than one type of biomass residue), determine $BF_{PJ,k,y}$ based on the specific circumstances of the project activity, thereby ensuring that the total quantity of all biomass residues types k used for heat generation as a result of the project activity is related to the increase in heat generation as a result of the project activity, as follows:

$$\sum_k BF_{PJ,k,y} \times NCV_k = \sum_k BF_{k,y} \times NCV_k \times \frac{HG_{PJ,biomass,y}}{HG_{PJ,biomass,total,y}} \quad \text{Equation (8)}$$

Where:

$BF_{PJ,k,y}$	=	Quantity of biomass residue types k used for heat generation as a result of the project activity during the year y (tons of dry matter or liter) ⁴
$BF_{k,y}$	=	Quantity of biomass residue types k fired in all units of heat generation equipment at the project site during the year y (tons of dry matter or liter) ⁴
NCV_k	=	Net calorific value of the biomass residue types k (GJ/ton of dry matter or GJ/liter)
$HG_{PJ,biomass,y}$	=	Heat generated with incremental biomass residues used as a result of the project activity during the year y (GJ/yr)
$HG_{PJ,biomass,total,y}$	=	Total heat generated from firing biomass residues in all heat generation equipment at the project site during the year y (GJ/yr)

5.4.2.1.1. Aerobic decay or uncontrolled burning of the biomass residues (cases B1 and B3)

44. If the most likely baseline scenario for the use of the biomass residues is either that the biomass residues would be dumped or left to decay under mainly aerobic conditions (case B1 as described in the tool “TOOL16: Project and leakage emissions from biomass”) or burnt in an uncontrolled manner without utilizing them for energy purposes (case B3 as described in the tool “TOOL16: Project and leakage emissions from biomass”), baseline

emissions are calculated assuming, for both scenarios viz., natural decay and uncontrolled burning, that the biomass residues would be burnt in an uncontrolled manner.

45. Baseline emissions are calculated by multiplying the quantity of biomass residues that would not be used in the absence of the project activity with the net calorific value and an appropriate emission factor, as follows:

$$BF_{BF,y} = GWP_{CH_4} \times \sum_k BF_{PJ,k,y} \times NCV_k \times EF_{burning,CH_4,k,y} \quad \text{Equation (9)}$$

Where:

$BF_{BF,y}$	=	Baseline emissions due to uncontrolled burning or decay of the biomass residues in year y (tCO ₂ e/yr)
GWP_{CH_4}	=	Global Warming Potential of methane valid for the commitment period (tCO ₂ e/tCH ₄)
$BF_{PJ,k,y}$	=	Quantity of biomass residue types k used for heat generation as a result of the project activity during the year y (tons of dry matter or liter) ⁴
NCV_k	=	Net calorific value of the biomass residue types k (GJ/ton of dry matter or GJ/liter)
$EF_{burning,CH_4,k,y}$	=	CH ₄ emission factor for uncontrolled burning of the biomass residue types k during the year y (tCH ₄ /GJ)
k	=	Types of biomass residues for which the identified baseline scenario is B1 or B3 as described in the tool "TOOL16: Project and leakage emissions from biomass"

46. To determine the CH₄ emission factor, project participants may undertake measurements or use referenced default values. In the absence of more accurate information, it is recommended to use 0.0027 t CH₄ per ton of biomass as default value for the product of NCV_k and $EF_{burning,CH_4,k,y}$.⁶
47. The uncertainty of the CH₄ emission factor is in many cases relatively high. In order to reflect this and for the purpose of providing conservative estimates of emission reductions, a conservativeness factor must be applied to the CH₄ emission factor. The level of the conservativeness factor depends on the uncertainty range of the estimate for the CH₄ emission factor. Appropriate conservativeness factors from Table 3 below shall be chosen and multiplied with the estimate for the CH₄ emission factor. For example, if the default CH₄ emission factor of 0.0027 t CH₄/t biomass is used, the uncertainty can be deemed to be greater than 100%, resulting in a conservativeness factor of 0.73. Thus, in this case an emission factor of 0.001971 t CH₄/t biomass should be used.

Table 3. Conservativeness factors

Estimated uncertainty range (%)	Assigned uncertainty band (%)	Conservativeness factor where lower values are more conservative
Less than or equal to 10	7	0.98

⁶ 2006 IPCC Guidelines, Volume 4, Table 2.5, default value for agricultural residues.

Estimated uncertainty range (%)	Assigned uncertainty band (%)	Conservativeness factor where lower values are more conservative
Greater than 10 and less than or equal to 30	20	0.94
Greater than 30 and less than or equal to 50	40	0.89
Greater than 50 and less than or equal to 100	75	0.82
Greater than 100	150	0.73

5.4.2.1.2. Anaerobic decay of the biomass residues (case B2)

48. If the most likely baseline scenario for the use of the biomass residues is that the biomass residues would decay under clearly anaerobic conditions (case B2 as described in the tool “TOOL16: Project and leakage emissions from biomass”), project participants shall calculate baseline emissions using the latest approved version of “TOOL04: Emissions from solid waste disposal sites”. The variable $BE_{CH\ 4,SWDS,y}$ calculated by the tool corresponds to $BE_{BF,y}$ in this methodology. Use as waste quantities prevented from disposal ($W_{j,x}$) in the tool those quantities of biomass residues ($BF_{PJ,k,y}$) for which B2 as described in the tool “TOOL16: Project and leakage emissions from biomass” has been identified as the most plausible baseline scenario.

5.4.2.1.3. Use for energy or feedstock purposes (cases B4 or B5)

49. The biomass residues would not decay or be burnt in an uncontrolled manner and $BE_{BF,y} = 0$.

5.5. Project emissions

50. For the purpose of determining GHG emissions of the CDM project activity, project participants shall include the following emissions sources:
- (a) Emissions from fossil fuel consumption at the project site related to the generation of heat;
 - (b) Emissions from grid-connected fossil fuel power plants in the electricity system for any electricity that is imported from the grid to the project site;
 - (c) Emissions from off-site transportation of biomass that are combusted in the project plant;
 - (d) If applicable, CH₄ emissions from combustion of biomass residues for heat generation at the project site;
 - (e) If applicable, emissions from anaerobic treatment of wastewater originating from the treatment of the biomass prior to combustion;
 - (f) If heat and/or power is produced from biomass cultivated in dedicated plantations: project emissions from cultivation of plantation (this source shall not be included if the total area of dedicated plantation is registered as one or several A/R CDM project activities).

51. Project emissions are calculated as follows:

$$PE_y = PE_{FF,y} + PE_{EC,y} + PE_{TR,y} + PE_{BF,y} + PE_{WW,y} + PE_{BG,y} + PE_{BC,y} \quad \text{Equation (10)}$$

Where:

PE_y	=	Project emissions during the year y (tCO ₂ /yr)
$PE_{FF,y}$	=	Emissions from on-site fossil fuel combustion at the project site in year y (tCO ₂ /yr)
$PE_{EC,y}$	=	Emissions from on-site electricity consumption at the project site in year y (tCO ₂ /yr)
$PE_{TR,y}$	=	Emissions from off-site transportation of biomass to the project site in year y (tCO ₂ /yr)
$PE_{BF,y}$	=	Emissions from combustion of biomass in the heat generation equipment in year y (tCO ₂ e/yr)
$PE_{WW,y}$	=	Emissions from wastewater generated from the treatment of biomass in year y (tCO ₂ e/yr)
$PE_{BG,y}$	=	Emissions from the production of biogas in year y (tCO ₂ e/yr)
$PE_{BC,y}$	=	Emissions associated with the cultivation of land to produce biomass in year y (tCO ₂ e/yr)

5.5.1. Emissions from on-site fossil fuel combustion ($PE_{FF,y}$)

52. Emissions from on-site fossil fuel combustion at the project site are calculated in accordance with the latest approved version of the “TOOL03: Tool to calculate project or leakage CO₂ emissions from fossil fuel combustion”. The parameter $PE_{FF,y}$ corresponds to $PE_{FC,j,y}$ in the tool, where j should include all processes of fuel combustion that are attributable to the project activity, such as for on-site transportation or treatment of the biomass residues. This should not include fossil fuels co-fired in the project heat generation equipment.

5.5.2. Emissions from on-site electricity consumption ($PE_{EC,y}$)

53. Emissions from on-site electricity consumption are calculated as follows:

$$PE_{EC,y} = EC_{PJ,y} \times EF_{grid,y} \quad \text{Equation (11)}$$

Where:

$PE_{EC,y}$	=	CO ₂ emissions from on-site electricity consumption at the project site in year y (tCO ₂ /yr)
$EC_{PJ,y}$	=	On-site electricity consumption at the project site in year y (MWh)
$EF_{grid,y}$	=	Grid emission factor in year y (tCO ₂ /MWh)

54. The Grid emission factor ($EF_{grid,y}$) shall be determined in accordance with “TOOL07: Tool to calculate the emission factor for an electricity system”.

5.5.3. Emissions from transportation of biomass to the project site ($PE_{TR,y}$)

55. In cases where the biomass residues are not generated directly at the project site, and always in the case of biomass from plantations, project participants shall determine CO₂ emissions resulting from transportation of the biomass to the project plant using the latest version of “TOOL12: Project and leakage emissions from transportation of freight”. $PE_{TR,m}$ in the tool corresponds to the parameter $PE_{TR,y}$ in this methodology and the monitoring period m is one year.

5.5.4. Emissions from combustion of biomass residues in the heat generation equipment ($PE_{BF,y}$)

56. If this source has been included in the project boundary, emissions are calculated as follows:

$$PE_{BF,y} = GWP_{CH_4} \times EF_{CH_4,BF} \times \sum_k BF_{PJ,k,y} \times NCV_k \quad \text{Equation (12)}$$

Where:

$PE_{BF,y}$	=	CH ₄ emissions from combustion of biomass residues in the heat generation equipment (tCH ₄ /yr)
GWP_{CH_4}	=	Global Warming Potential of methane valid for the commitment period (tCO ₂ /tCH ₄)
$EF_{CH_4,BF}$	=	CH ₄ emission factor for the combustion of the biomass residues in the heat generation equipment (tCH ₄ /GJ)
$BF_{PJ,k,y}$	=	Quantity of biomass residue types k used for heat generation as a result of the project activity during the year y (tons of dry matter or liter) ⁴
NCV_k	=	Net calorific value of the biomass residue types k (GJ/ton of dry matter or GJ/liter)

57. To determine the CH₄ emission factor, project participants may conduct measurements at the plant site or use IPCC default values, as provided in Table 4 below. The uncertainty of the CH₄ emission factor is in many cases relatively high. In order to reflect this and for the purpose of providing conservative estimates of emission reductions, a conservativeness factor must be applied to the CH₄ emission factor. The level of the conservativeness factor depends on the uncertainty range of the estimate for the CH₄ emission factor. Appropriate conservativeness factor from Table 5 below shall be chosen to multiply with the estimate for the CH₄ emission factor.
58. For example, where the default CH₄ emission factor of 30 kg/TJ from Table 4 below is used, the uncertainty is estimated to be 300%, resulting in a conservativeness factor of 1.37. Thus, in this case a CH₄ emission factor of 41.1 kg/TJ should be used.

Table 4. Default CH₄ emission factors for combustion of biomass residues⁷

	Default emission factor (kg CH ₄ / TJ)	Assumed uncertainty
Wood waste	30	300%
Sulphite lyes (Black Liquor)	3	300%
Other solid biomass residues	30	300%
Liquid biomass residues	3	300%

Table 5. Conservativeness factors

Estimated uncertainty range (%)	Assigned uncertainty band (%)	Conservativeness factor where higher values are more conservative
Less than or equal to 10	7	1.02
Greater than 10 and less than or equal to 30	20	1.06
Greater than 30 and less than or equal to 50	40	1.12
Greater than 50 and less than or equal to 100	75	1.21
Greater than 100	150	1.37

5.5.5. Emissions from wastewater generated from the treatment of biomass ($PE_{WW,y}$)

59. This emission source should be estimated in cases where wastewater originating from the treatment of the biomass is (partly) treated under anaerobic conditions and where methane from the waste water is not captured and flared or combusted. Project emissions from waste water are estimated as follows:

$$PE_{WW,y} = GWP_{CH_4} \times V_{WW,y} \times COD_{WW,y} \times B_{o,WW} \times MCF_{WW} \quad \text{Equation (13)}$$

Where:

$PE_{WW,y}$	= Emissions from wastewater generated from the treatment of biomass in year y (tCO ₂ e)
GWP_{CH_4}	= Global Warming Potential of methane valid for the commitment period (tCO ₂ /tCH ₄)
$V_{WW,y}$	= Quantity of waste water generated in year y (m ³)
$COD_{WW,y}$	= Average chemical oxygen demand of the waste water in year y (tCOD/m ³)
$B_{o,WW}$	= Methane generation potential of the waste water treatment system (t CH ₄ /tCOD)
MCF_{WW}	= Methane correction factor for the waste water (ratio)

⁷ Values are based on the 2006 IPCC Guidelines, Volume 2, Chapter 2, Tables 2.2 to 2.6.

5.5.6. Emissions from the production of biogas in year y ($PE_{BG,y}$)

60. In case the project includes biogas the consideration of project emissions associated with the production of biogas depends on the selected baseline scenario for biogas and whether the biogas is sourced from a registered CDM project activity according to the following provisions:
- (a) In case the biogas is provided by a registered CDM project activity, the project emissions will be covered in the PDD of the registered CDM project activity;
 - (b) In case the biogas is not provided by a registered CDM project activity:
 - (i) If baseline scenario BG1 is selected, the project emissions should be included in this proposed CDM project activity. The emission source shall include project emissions from physical leakage of methane from the anaerobic digester, from treatment of wastewater effluent from the anaerobic digester (where applicable), and from land application of sludge (where applicable). The estimation of these emission sources shall follow the procedures for these sources as identified in the project emissions section of ACM0014 or AMS-III.H.;
 - (ii) In case of baseline scenario BG2 and/or BG3, no project emissions need to be included.

5.5.7. Emissions associated with the cultivation of land to produce biomass in year y ($PE_{BC,y}$)

61. If the project includes biomass from dedicated plantations, the associated emissions shall be calculated according to "TOOL16: Project and leakage emissions from biomass".

5.6. Leakage

62. Leakage emissions due to diversion of biomass residues from other uses applications shall be calculated according to "TOOL16: Project and leakage emissions from biomass".
63. Leakage emissions due to shift of pre-project activities shall be calculated according to "TOOL16: Project and leakage emissions from biomass".
64. In the case that negative overall emission reductions arise in a year through application of the leakage emissions, CERs are not issued to project participants for the year concerned and in subsequent years, until emission reductions from subsequent years have compensated the quantity of negative emission reductions from the year concerned. For example, if negative emission reductions of 30 tCO₂e occur in the year t and positive emission reductions of 100 tCO₂e occur in the year $t+1$, only 70 CERs are issued for the year $t+1$.

5.7. Emission reductions

65. Emission reductions are calculated as follows:

$$ER_y = BE_y - PE_y - LE_y \quad \text{Equation (14)}$$

Where:

ER_y	=	Emission reductions during the year y (tCO ₂ /yr)
BE_y	=	Baseline emissions during the year y (tCO ₂ /yr)
PE_y	=	Project emissions during the year y (tCO ₂ /yr)
LE_y	=	Leakage emissions during the year y (tCO ₂ /yr)

5.8. Changes required for methodology implementation in 2nd and 3rd crediting periods

66. Consistent with guidance by the Executive Board, project participants shall assess the continued validity of the baseline and update the baseline applying the latest version of the tool “TOOL11: Assessment of the validity of the original/current baseline and update of the baseline at the renewal of a crediting period”.

5.9. Data and parameters not monitored

Data / Parameter table 1.

Data / Parameter:	GWP_{CH4}
Data unit:	tCO ₂ e/tCH ₄
Description:	GWP_{CH4} = Global Warming Potential of methane valid for the commitment period (tCO ₂ /tCH ₄)
Source of data:	IPCC
Measurement procedures (if any):	Default value of 25 from IPCC Fourth Assessment Report (AR4). Shall be updated according to any future COP/MOP decisions
Any comment:	-

Data / Parameter table 2.

Data / Parameter:	$\eta_{heat,FF}$
Data unit:	Ratio
Description:	Average net efficiency of the heat generation equipment if fired with fossil fuels in the baseline
Source of data:	Determined using the latest approved version of the tool “TOOL09: Determining the baseline efficiency of thermal or electric energy generation systems” or assume an efficiency of 100% as a conservative default value
Measurement procedures (if any):	Document measurement procedures and results and manufacturer’s information transparently in the CDM-PDD
Any comment:	-

Data / Parameter table 3.

Data / Parameter:	$HG_{biomass,historic,n}/HG_{biomass,historic,n-1}/HG_{biomass,historic,n-2}$
Data unit:	GJ/yr

Description:	Historical annual heat generation from firing biomass at the project site during the year n , $n-1$ or $n-2$, where n corresponds to the year prior to the implementation of the project activity
Source of data:	Onsite measurements
Measurement procedures (if any):	<p>Heat generation can be determined as per section 5.5.1.2.2 (Case B) or as the difference of the enthalpy of the steam or hot fluid and/or gases generated by the heat generation equipment and the sum of the enthalpies of the feed-fluid and/or gases, blow-down and any condensate returns. The respective enthalpies should be determined based on the mass (or volume) flows, the temperatures and, in case of superheated steam, the pressure. Steam tables or appropriate thermodynamic equations may be used to calculate the enthalpy as a function of temperature and pressure.</p> <p>In case of equipment that produces hot water/oil this is expressed as difference in the enthalpy between the hot water/oil supplied to and returned by the plant</p> <p>In case of equipment that produces hot gases or combustion gases, this is expressed as difference in the enthalpy between the hot gas produced and all streams supplied to the plant. The enthalpy of all relevant streams shall be determined based on the mass flow, temperature, pressure, density and specific heat of the gas.</p>
Any comment:	If the three most recent historical years prior to the implementation of the project activity are not representative for the situation at the project site (e.g. a drought in one year, an equipment or plant not operating during a certain year for technical reasons, etc.), project participants may alternatively select the five most recent historical years from which one year may be excluded if deviating significantly from other years. The selection by project participants should be documented in the CDM-PDD and be applied to all relevant provisions and equations throughout this methodology in a consistent manner, including the applicability condition

Data / Parameter table 4.

Data / Parameter:	$BF_{k,n}/BF_{k,n-1}/BF_{k,n-2}$
Data unit:	Tons of dry matter or liter ⁴
Description:	Quantity of biomass types k fired in all heat generation equipment at the project site during the historical year n , $n-1$ or $n-2$, where n corresponds to the year prior to implementation of the project activity
Source of data:	On-site measurements
Measurement procedures (if any):	Use weight or volume meters. Adjust for the moisture content in order to determine the quantity of dry biomass. The quantity shall be cross-checked with the quantity of heat generated and any fuel purchase receipts (if available)

Any comment:	If the three most recent historical years prior to the implementation of the project activity are not representative for the situation at the project site (e.g. a drought in one year, equipment not operating during a certain year for technical reasons, etc.), project participants may alternatively select the five most recent historical years from which one year may be excluded if deviating significantly from other years. The selection by project participants should be documented in the CDM-PDD and be applied to all relevant provisions and equations throughout this methodology in a consistent manner, including the applicability condition
--------------	--

Data / Parameter table 5.

Data / Parameter:	$FC_{i,n}/FC_{i,n-1}/FC_{i,n-2}$
Data unit:	Mass or volume unit ⁵
Description:	Quantity of fossil fuel types <i>i</i> fired in all heat generation equipment at the project site during the historical year <i>n</i> , <i>n-1</i> or <i>n-2</i> , where <i>n</i> corresponds to the year prior to implementation of the project activity
Source of data:	On-site measurements
Measurement procedures (if any):	Use weight or volume meters. The quantity shall be cross-checked with the quantity of heat generated and any fuel purchase receipts (if available)
Any comment:	If the three most recent historical years prior to the implementation of the project activity are not representative for the situation at the project site (e.g. a drought in one year, an equipment not operating during a certain year for technical reasons, etc.), project participants may alternatively select the five most recent historical years from which one year may be excluded if deviating significantly from other years. The selection by project participants should be documented in the CDM-PDD and be applied to all relevant provisions and equations throughout this methodology in a consistent manner, including the applicability condition

Data / Parameter table 6.

Data / Parameter:	EG_{hist}
Data unit:	MWh
Description:	Highest historical electricity generation at the project site during the most recent three years prior to the implementation of the project activity
Source of data:	On-site measurements
Measurement procedures (if any):	-
Any comment:	Required to assess the applicability condition referring to power generation at the project site

6. Monitoring methodology

67. Describe and specify in the CDM-PDD all monitoring procedures, including the type of measurement instrumentation used, the responsibilities for monitoring and QA/QC

procedures that will be applied. Where the methodology provides different options (e.g. use of default values or on-site measurements), specify which option will be used. All meters and instruments should be calibrated regularly as per industry practices.

68. In addition to the parameters and procedures described herein, relevant monitoring provisions contained in the tools referred to in this methodology also apply.

6.1. Data and parameters monitored

Data / Parameter table 7.

Data / Parameter:	$EF_{FF,CO_2,y}$
Data unit:	tCO ₂ e/GJ
Description:	CO ₂ emission factor of the fossil fuel type displaced by biomass for the year <i>y</i>
Source of data:	Either conduct measurements or use accurate and reliable local or national data where available. Where such data is not available, use IPCC default emission factors (country-specific, if available) if they are deemed to reasonably represent local circumstances. Choose the value in a conservative manner and justify the choice
Measurement procedures (if any):	Measurements shall be carried out at reputed laboratories and according to relevant international standards
Monitoring frequency:	In case of measurements: At least every six months, taking at least three samples for each measurement. In case of other data sources: Review the appropriateness of the annual data
QA/QC procedures:	Check consistency of measurements and local/national data with default values by the IPCC. If the values differ significantly from IPCC default values, collect additional information or conduct additional measurements
Any comment:	For the purpose of determining $EF_{FF,CO_2,y}$, as a conservative approach, the least carbon intensive fuel type should be used among the fossil fuels types used at the project site during the most recent 3 years prior to the implementation of the project activity and the fossil fuels used in the equipment at the project site due the year <i>y</i>

Data / Parameter table 8.

Data / Parameter:	$HG_{PJ,total,y}$
Data unit:	GJ/yr
Description:	Total heat generated in all heat generation equipment at the project site, using both biomass and fossil fuels, during the year <i>y</i>
Source of data:	On-site measurements

Measurement procedures (if any):	Heat generation is determined as the difference of the enthalpy of the steam or hot fluid and/or gases generated by the heat generation equipment and the sum of the enthalpies of the feed-fluid and/or gases blow-down and any condensate returns. The respective enthalpies should be determined based on the mass (or volume) flows, the temperatures and, in case of superheated steam, the pressure. Steam tables or appropriate thermodynamic equations may be used to calculate the enthalpy as a function of temperature and pressure. In case of equipment that produces hot water/oil this is expressed as difference in the enthalpy between the hot water/oil supplied to and returned by the plant. In case of equipment that produces hot gases or combustion gases, this is expressed as difference in the enthalpy between the hot gas produced and all streams supplied to the plant. The enthalpy of all relevant streams shall be determined based on the monitored mass flow, temperature, pressure, density and specific heat of the gas
Monitoring frequency:	Continuously, aggregated annually
QA/QC procedures:	The consistency of metered net heat generation should be cross-checked with the quantity of biomass and/or fossil fuels fired (e.g. check whether the net heat generation divided by the quantity of fuel fired results in a reasonable thermal efficiency that is comparable to previous years)
Any comment:	The parameters mass flow, temperature, pressure, density and specific heat of the gas, shall be monitored

Data / Parameter table 9.

Data / Parameter:	$BF_{k,y}$
Data unit:	Tons of dry matter or liter ⁴
Description:	Quantity of biomass types k fired in all units of heat generation equipment at the project site during the year y
Source of data:	On-site measurements
Measurement procedures (if any):	Use weight or volume meters. Adjust for the moisture content in order to determine the quantity of dry biomass. The quantity shall be crosschecked with the quantity of heat generated and any fuel purchase receipts (if available)
Monitoring frequency:	Continuously, aggregated at least annually
QA/QC procedures:	Crosscheck the measurements with an annual energy balance that is based on purchased quantities and stock changes
Any comment:	The quantity of biomass combusted should be collected separately for all types of biomass. For biogas the volume shall be referred to Normal Temperature and Pressure conditions (NTP).

Data / Parameter table 10.

Data / Parameter:	Moisture content
Data unit:	%
Description:	Moisture content of each biomass types k
Source of data:	On-site measurements

Measurement procedures (if any):	-
Monitoring frequency:	The moisture content should be monitored for each batch of biomass of homogeneous quality The weighted average should be calculated for each monitoring period and used in the calculations
QA/QC procedures:	-
Any comment:	In case of dry biomass, monitoring of this parameter is not necessary

Data / Parameter table 11.

Data / Parameter:	$FC_{i,y}$
Data unit:	Mass or volume unit ⁵
Description:	Quantity of fossil fuel types <i>i</i> fired in all heat generation equipment at the project site during the year <i>y</i>
Source of data:	On-site measurements
Measurement procedures (if any):	-
Monitoring frequency:	Continuously, aggregated at least annually
QA/QC procedures:	Cross-check the measurements with an annual energy balance that is based on purchased quantities and stock changes
Any comment:	The quantity of fossil fuels combusted should be collected separately for all types of fossil fuels.

Data / Parameter table 12.

Data / Parameter:	$EC_{PJ,y}$
Data unit:	MWh
Description:	On-site electricity consumption attributable to the project activity during the year <i>y</i>
Source of data:	On-site measurements
Measurement procedures (if any):	Use electricity meters. The quantity shall be cross-checked with electricity purchase receipts
Monitoring frequency:	Continuously, aggregated at least annually
QA/QC procedures:	Cross-check measurement results with invoices for purchased electricity if available
Any comment:	-

Data / Parameter table 13.

Data / Parameter:	$EF_{grid,y}$
Data unit:	tCO ₂ /MWh
Description:	CO ₂ emission factor for electricity used from the grid
Source of data:	Use "TOOL07: Tool to calculate the emission factor for an electricity system" to calculate the grid emission factor
Measurement procedures (if any):	-

Monitoring frequency:	Either once at the start of the project activity or updated annually, consistent with guidance provided in the tool
QA/QC procedures:	As per the guidance provided in the tool
Any comment:	All data and parameters to determine the grid electricity emission factor, as required by the tool, shall be included in the monitoring plan

Data / Parameter table 14.

Data / Parameter:	NCV_i
Data unit:	GJ/mass or volume unit
Description:	Net calorific value of fossil fuel types <i>i</i>
Source of data:	Either conduct measurements or use accurate and reliable local or national data where available. Where such data is not available, use IPCC default net calorific values (country-specific, if available) if they are deemed to reasonably represent local circumstances. Choose the values in a conservative manner and justify the choice
Measurement procedures (if any):	Measurements shall be carried out at reputed laboratories and according to relevant international standards
Monitoring frequency:	In case of measurements: At least every six months, taking at least three samples for each measurement In case of other data sources: Review the appropriateness of the data annually
QA/QC procedures:	Check consistency of measurements and local / national data with default values by the IPCC. If the values differ significantly from IPCC default values, collect additional information or conduct additional measurements
Any comment:	-

Data / Parameter table 15.

Data / Parameter:	NCV_k
Data unit:	GJ/ton of dry matter or GJ/liter
Description:	Net calorific value of biomass types <i>k</i>
Source of data:	Measurements/calculations
Measurement procedures (if any):	Measurements shall be carried out at reputed laboratories and according to relevant international standards. Measure/calculate the NCV based on dry biomass
Monitoring frequency:	At least every six months, taking at least three samples for each measurement
QA/QC procedures:	Check the consistency of the measurements by comparing the measurement results with measurements from previous years, relevant data sources (e.g. values in the literature, values used in the national GHG inventory) and default values by the IPCC. If the measurement results differ significantly from previous measurements or other relevant data sources, conduct additional measurements. Ensure that the NCV is determined on the basis of dry biomass
Any comment:	Biogas should be included as appropriate if applicable (in which case convenient units such as GJ/m ³ should be used)

Data / Parameter table 16.

Data / Parameter:	$EF_{CH_4,BF}$
Data unit:	kg CH ₄ / TJ
Description:	CH ₄ emission factor for the combustion of the biomass residues in the heat generation equipment
Source of data:	On-site measurements or default values, as provided in Table 4
Measurement procedures (if any):	The CH ₄ emission factor may be determined based on a stack gas analysis using calibrated analyzers
Monitoring frequency:	At least quarterly, taking at least three samples per measurement
QA/QC procedures:	Check the consistency of the measurements by comparing the measurement results with measurements from previous years, relevant data sources (e.g. values in the literature, values used in the national GHG inventory) and default values by the IPCC. If the measurement results differ significantly from previous measurements or other relevant data sources, conduct additional measurements
Any comment:	Monitoring of this parameter for project emissions is only required if CH ₄ emissions from biomass combustion are included in the project boundary. Note that a conservative factor shall be applied, as specified in the baseline methodology

Data / Parameter table 17.

Data / Parameter:	$EF_{burning,CH_4,k,y}$
Data unit:	tCH ₄ /GJ
Description:	CH ₄ emission factor for uncontrolled burning of the biomass residue types <i>k</i> during the year <i>y</i>
Source of data:	Undertake measurements or use referenced and reliable default values (e.g. IPCC)
Measurement procedures (if any):	Project participants may undertake measurements or use referenced default values. In the absence of more accurate information, it is recommended to use 0.0027 t CH ₄ per ton of biomass as default value for the product of NCV_k and $EF_{burning,CH_4,k,y}$
Monitoring frequency:	Review of default values: annually Measurements: once at the start of the project activity
QA/QC procedures:	Cross-check the results of any measurements with IPCC default values. If there is a significant difference, check the measurement method and increase the number of measurements in order to verify the results
Any comment:	Monitoring of this parameter for project emissions is only required if CH ₄ emissions from biomass combustion are included in the project boundary. Note that a conservative factor shall be applied, as specified in the baseline methodology

Data / Parameter table 18.

Data / Parameter:	$EF_{CO_2,LE}$
Data unit:	tCO ₂ /GJ
Description:	CO ₂ emission factor of the most carbon intensive fuel used in the country

Source of data:	Identify the most carbon intensive fuel type from the national communication, other literature sources (e.g. IEA). Possibly consult with the national agency responsible for the national communication/GHG inventory. If available, use national default values for the CO ₂ emission factor. Otherwise, IPCC default values may be used
Measurement procedures (if any):	-
Monitoring frequency:	Annually
QA/QC procedures:	-
Any comment:	-

Data / Parameter table 19.

Data / Parameter:	EG_y
Data unit:	MWh
Description:	Electricity generation during the year y at the project site
Source of data:	On-site measurements
Measurement procedures (if any):	-
Monitoring frequency:	Annual
QA/QC procedures:	-
Any comment:	Monitoring of this parameters is only required if power is generated at the project site. In this case, monitoring is needed to assess whether the applicability condition referring to power generation at the project site is met

Data / Parameter table 20.

Data / Parameter:	$V_{ww,y}$
Data unit:	m ³
Description:	Quantity of waste water generated in year y
Source of data:	On-site measurements
Measurement procedures (if any):	-
Monitoring frequency:	Data monitored continuously and aggregated as appropriate, to calculate emissions reductions
QA/QC procedures:	-
Any comment:	-

Data / Parameter table 21.

Data / Parameter:	$COD_{ww,y}$
Data unit:	tCOD/m ³
Description:	Average chemical oxygen demand of the waste water in year y
Source of data:	On-site measurements

Measurement procedures (if any):	-
Monitoring frequency:	In case of measurements: At least every six months, taking at least three samples for each measurement
QA/QC procedures:	-
Any comment:	-

- - - - -

Document information

<i>Version</i>	<i>Date</i>	<i>Description</i>
05.0	31 August 2018	EB 100, Annex 3 Revision to include reference to TOOL16.
04.0	2 March 2012	EB 66, Annex 38 Revision in order to incorporate reference to the tools: <ul style="list-style-type: none"> • “Assessment of the validity of the original/current baseline and update of the baseline at the renewal of a crediting period”; • “Tool for project and leakage emissions from road transportation of freight”. In addition, the leakage section was modified, providing for a simpler procedure, and some minor editorial improvements were made.
03.0	04 December 2009	EB 51, Annex 6 Revision to: <ul style="list-style-type: none"> • Revise the applicability of the methodology to cover a broader range of heat generation equipment in addition to boilers; • References to the latest approved methodological tools were included; • To insert the correct sectoral scopes; • To clarify monitoring requirement of moisture of biomass; • To clarify that NCV of biomass can be calculated and need not only be measured; • Several minor editorial revisions were made.
02.2	17 July 2009	EB 48, Annex 8 Editorial revision to clarify that: (i) in the case of fossil fuels co-fired with biomass, the fossil fuel amount shall not exceed 50% of the total fuel fired on an energy basis; and (ii) for the purpose of this methodology, refuse derived fuel / refuse plastic fuel (RDF/RPF) should be considered as fossil fuels.
02.1	02 August 2008	EB 41, Paragraph 26(g)

AM0036

Large-scale Methodology: Fuel switch from fossil fuels to biomass in heat generation equipment

Version 05.0

Sectoral scope(s): 01 and 04

<i>Version</i>	<i>Date</i>	<i>Description</i>
		The title of the “Tool to determine methane emissions avoided from dumping waste at a solid waste disposal site” changes to “Tool to determine methane emissions avoided from disposal of waste at a solid waste disposal site”.
02.0	27 July 2007	EB 33, Annex 9 Revision to correct an oversight where in the avoidance of methane emissions from anaerobic decay of biomass is credited even for that fraction of biomass, which is identified as not being surplus and thus would not have been dumped and thereby not causing methane emissions.
01.0	29 September 2006	EB 26, Annex 3 Initial adoption.

Decision Class: Regulatory
Document Type: Standard
Business Function: Methodology
Keywords: biomass, fuel switching, heat generation, retrofit
