



Indicative simplified baseline and monitoring methodologies  
for selected small-scale CDM project activity categories

**TYPE III - OTHER PROJECT ACTIVITIES**

Project participants shall apply the general guidance to the small-scale CDM methodologies, information on additionality (attachment A to appendix B) provided at <http://cdm.unfccc.int/methodologies/SSCmethodologies/approved.html> > *mutatis mutandis*.

**III.AG. Switching from high carbon intensive grid electricity to low carbon intensive fossil fuel****Technology/measure**

1. This methodology comprises switch from a carbon intensive energy source (or mix of energy sources) to a single low carbon intensive energy source in existing and new industrial, residential, commercial, and institutional for electricity generation applications. This methodology is applicable only if the sole energy source or one of the energy sources in the baseline is high carbon intensive grid electricity (e.g., switch from a diesel based captive electricity generation complemented by a grid electricity import to a natural gas based captive electricity generation)<sup>1</sup>.
2. Energy source switch may be in a single element process or may include several element processes within the facility<sup>2</sup>. Non-element processes (e.g., gas turbine with heat recovery) are also included under this methodology, provided that emission reductions are only claimed for one of the outputs i.e., electricity<sup>3</sup>. Multiple fossil fuels switching in an element process is not covered under this methodology; however project proponents may explore applying AMS-III.AH.
3. This methodology is applicable for retrofit or replacement of existing installations<sup>4</sup>, as well as for Greenfield and capacity expansion project activities.
4. Switching of energy sources may also result in energy efficiency improvements of the facility, thus both the project activities with or without energy efficiency improvements are eligible under this category. Project activities for implementation of energy efficiency measures not-related to the switch of energy sources shall apply Type II SSC methodologies.
5. This methodology is not applicable to project activities that propose switch from fossil fuel use in the baseline to renewable biomass, biofuel or renewable energy in the project scenario. This methodology is not applicable to project activities utilising waste gas or energy; these project activities may consider applying AMS-III.Q.
6. This category is applicable to project activities where it is possible to directly measure and record the energy use/output and consumption (e.g., fossil fuel) within the project boundary.

<sup>1</sup> Cases involving shift to low GHG intensive grid electricity may be submitted through the request for revision process.

<sup>2</sup> An “*element process*” is defined as fuel combustion, energy conversion or energy use in single equipment. Each element process generates a single output (such as steam or electricity) by using a single energy source. This methodology covers switch of energy sources in several element processes, i.e., project participants may submit one CDM-PDD for fuel switch in several element processes within a facility.

<sup>3</sup> As an example gas firing combustion engines with heat recovery are not considered element processes as they produce electricity as well as recovered heat energy as output.

<sup>4</sup> I.e., the project capacity is within  $\pm 20$  % of the baseline installed capacity.



**Indicative simplified baseline and monitoring methodologies  
for selected small-scale CDM project activity categories**

*III.AG. Switching from high carbon intensive grid electricity to low carbon intensive fossil fuel  
(cont)*

---

7. Electricity produced under the project activity shall be for on-site captive use and/or export to other facilities included in the project boundary. In case energy produced by the project activity is delivered to another facility, or facilities, within the project boundary, a contract between the supplier and consumer(s) of the energy will have to be entered into specifying that only the facility generating the energy can claim emission reductions from the energy displacement.
8. Export of electricity to a grid is not eligible under this category. That is, the project activity may physically connect to a grid but emission reduction can not be claimed by exporting electricity to the grid.
9. Measures are limited to those that result in emission reductions of less than or equal to 60 kt CO<sub>2</sub> equivalent annually.
10. The project activity does not result in integrated process change. The purpose is to exclude measures that affect other characteristics of the process besides switch of energy sources e.g., operational conditions, type of raw material processed, use of non-energy additives, change in type or quality of products manufactured etc.
11. For the purpose of this methodology, natural gas is defined as a gas which consists primarily of methane and which is generated from (i) natural gas fields (non-associated gas), (ii) associated gas found in oil fields. It may be blended up to 1% on a volume basis with gas from other sources, such as, *inter alia*, biogas generated in biodigesters, gas from coal mines, gas which is gasified from solid fossil fuels, etc.<sup>5</sup>

### **Boundary**

12. The project boundary is the physical, geographical site where the fossil fuel switching takes place, and all installations affected by the switching.
13. All power plants connected physically to the baseline grid as defined in “Tool to calculate emission factor for an electricity system” shall be included in the project boundary.

### **Baseline**

14. If during the crediting period, total annual production of electricity for existing system does not increase by more than 20% from the established baseline values<sup>6</sup> during the crediting period then the baseline scenario is the continuation of the operation of the existing systems.
15. If during the crediting period, total annual production of electricity for existing system does increase beyond 20% from the established baseline values then one of the following shall be used for determining baseline scenario:

---

<sup>5</sup> This limitation is included because the methodology does not provide procedures to estimate the GHG emissions associated with the production of gas from these other sources. Project activities that use gas that does not comply with this definition must apply for a revision of the methodology.

<sup>6</sup> Baseline emissions are established from the characteristics of the existing systems using data from the immediately prior three years as described in paragraph 19.



**Indicative simplified baseline and monitoring methodologies  
for selected small-scale CDM project activity categories**

*III.AG. Switching from high carbon intensive grid electricity to low carbon intensive fossil fuel  
(cont)*

---

- (a) If it can be demonstrated, using the related and relevant procedures prescribed in the SSC general guidance, that the most plausible baseline scenario for the supply of additional amounts of energy is the same as the existing applications then such applications can be continued to be used for determining baseline emissions.
- (b) If it cannot be demonstrated that the most plausible baseline scenario for the supply of additional amounts of energy is the same as the existing applications then the Baseline Reference Plant Approach, as defined below shall be used.

16. If, irrespective of total annual energy production of baseline or project scenarios, it is determined that new and more efficient systems (as compared to the existing systems) would have been installed in the absence of the project activity (for example, due to the baseline equipment reaching the end of its useful life at any point during the crediting period) then the Baseline Reference Plant Approach, as defined below, shall be used.

17. Replacing system that would have been built: The project consists of the installation of a new system that replace the operation of systems that would have been built and utilized. In such cases the Baseline Reference Plant Approach, as defined below, shall be used to define the baseline scenario.

**Baseline Reference Plant Approach**

18. In cases where the baseline scenario consists of the installation of new systems and/or the utilization of new energy sources, a Reference Plant shall be defined as the baseline scenario. The Reference Plant shall be based on common practice for similar industrial, residential, commercial, and institutional energy generation systems and sources in the same sector and in the same country or region as the project. The identification of the Reference Plant should exclude plants implemented as CDM project activities. In cases where no such plant exists within the region, the economically most attractive technology and fuel type should be identified among those which provide the same service, that are technologically available, and that are in compliance with relevant regulations. The efficiency of the technology should be selected in a conservative manner, i.e., where several technologies could be used and are similarly economically attractive, the most efficient technology should be defined as the baseline scenario. In addition, the least carbon intensive fuel type should be chosen in case of multiple fuels being possible choices.

19. For existing facilities, historical information (detailed records) on the use of energy sources (e.g., electricity, fossil fuel) and the plant output (i.e., electricity) in the baseline captive energy generation plant from at least 3 years prior to project implementation shall be used in the baseline calculations, e.g., liquid fuel oil use and electricity generated by a generating unit (records of fuel used and output can be used *in lieu* of actual collecting baseline validation data<sup>7</sup>). For facilities that are less than 3 years old, all historical data shall be available (a minimum of one year data would be required). In case of project activity exporting to other facilities included in the project boundary, the above historical information from the recipient plants are required.

---

<sup>7</sup> In the case of coal, the emission coefficient shall be based on test results for periodic samples of the coal purchased if such tests are part of the normal practice for coal purchases.



Indicative simplified baseline and monitoring methodologies  
for selected small-scale CDM project activity categories

*III.AG. Switching from high carbon intensive grid electricity to low carbon intensive fossil fuel (cont)*

20. Baseline emissions shall be determined as follows:

$$BE_y = EF_{BL} * Q_{PJ,y} \quad (1)$$

Where:

$BE_y$	Baseline emissions in the project activity in year $y$ (tCO <sub>2</sub> )
$EF_{BL}$	Emission factor for the baseline situation (e.g., tCO <sub>2</sub> /MWh)
$Q_{PJ,y}$	Net electricity output in the project activity in year $y$ (e.g., MWh)

21. The determination of the baseline emission factor for electricity generation depends on the baseline scenario identified.

22. If the identified baseline is the continuation of the current practice the emission factor of captive plants ( $EF_{BL,captive}$ ) is determined based on the historical information as follows:

$$EF_{BL,captive} = \frac{(FC_{BL,captive} * NCV_{FF} * EF_{FF,CO2})}{Q_{BL,captive}} \quad (2)$$

Where:

$FC_{BL,captive}$	Amount of fuel consumed for captive electricity generation in the baseline situation in accordance with paragraph 19 (mass or volume unit)
$EF_{FF,CO2}$	CO <sub>2</sub> emission factor for the baseline fossil fuel (tCO <sub>2</sub> /TJ)
$NCV_{FF}$	Net calorific value for the baseline fossil fuel (TJ/ mass or volume unit) <sup>8</sup>
$Q_{BL,captive}$	Net electricity output in the baseline situation during the corresponding period of time for which the total fuel consumption was taken, in accordance with paragraph 19 (MWh)

23. If the identified baseline scenario includes reference captive plant, (i.e., in the absence of the project activity, the electricity demand of consumers is met through a new captive fossil fuel fired power plant “reference plant”), the emission factor for the baseline electricity generation from the reference plant ( $EF_{BL,captive}$ ) is calculated as per the procedures described in the latest version of “Tool to calculate baseline, project and/or leakage emissions from electricity consumption”.

24. In the absence of the project activity, if electricity is sourced from grid the emission factor for the baseline electricity supply correspond to the grid emission factor. The baseline grid

<sup>8</sup> Reliable local or national data for the NCV shall be used; IPCC default values should be used only when country or project specific data are not available or difficult to obtain.



**Indicative simplified baseline and monitoring methodologies  
for selected small-scale CDM project activity categories**

*III.AG. Switching from high carbon intensive grid electricity to low carbon intensive fossil fuel  
(cont)*

emission factor ( $EF_{BL,grid}$ ) shall be estimated based on the procedures described under “Tool to calculate emission factor for an electricity system”.

25. In the absence of the project activity, if electricity is sourced from the combination of the grid and captive power plant, a combined emission factor for an existing captive power plant and grid has to be determined. The share of contributions has to be determined using historical information over the three years period prior to the project activity ( $EF_{BL,weighted}$ ), e.g., if the captive power plant provided 30% of the electricity and the grid 70%, the emission factor should be calculated based on this historical allocation. For new facilities, the most conservative (lowest) emission factor of the two electricity sources should be used, as it is difficult to determine and justify the ratio sources of the hypothetical electricity supply.

#### **Project Activity Emissions**

26. Project activity emissions consist of those emissions related with the use of fossil fuel after the fuel switch. Project emissions are to be determined as per the “Tool to calculate project or leakage CO<sub>2</sub> emissions from fossil fuel combustion”.

#### **Leakage**

27. If the energy generating equipment is transferred from another activity, leakage is to be considered.

#### **Emission Reductions**

28. The emission reduction achieved by the project activity will be calculated as the difference between the baseline emissions and the project emissions.

$$ER_y = BE_y - PE_y - LE_y \quad (3)$$

Where:

$ER_y$  Emission reductions in the year  $y$  (tCO<sub>2</sub>e)

#### **Monitoring**

29. Monitoring shall include the following parameters as per the table 1 below:



Indicative simplified baseline and monitoring methodologies  
for selected small-scale CDM project activity categories

Table 1: Parameters for monitoring during the crediting period

No.	Parameter	Description	Unit	Monitoring/ recording Frequency	Measurement Methods and Procedures
1	$Q_{PJ,y}$	Net electricity output in the project activity in year $y$	MWh	Continuous monitoring, hourly measurement and at least monthly recording	Measurements are undertaken using energy meters Calibration should be undertaken as prescribed in the related and relevant paragraph of General Guidelines to SSC Methodologies
2	$EF_{BL, grid}$	CO <sub>2</sub> emission factor for the grid electricity in year $y$	t CO <sub>2</sub> e/ kWh	As per the “Tool to calculate emission factor for an electricity system”.	As per the “Tool to calculate emission factor for an electricity system”
3	$FC_{PJ,y}$	Quantity of fossil fuel combusted in year $y$	Mass or volume unit	As per the “Tool to calculate project or leakage CO <sub>2</sub> emissions from fossil fuel combustion”	As per the “Tool to calculate project or leakage CO <sub>2</sub> emissions from fossil fuel combustion”



**Indicative simplified baseline and monitoring methodologies  
for selected small-scale CDM project activity categories**

---

**Project activity under a programme of activities**

The following conditions apply for use of this methodology in a project activity under a programme of activities:

30. Leakage emissions resulting from fuel extraction, processing, liquefaction, transportation, re-gasification and distribution of fossil fuels outside of the project boundary shall be considered, as per the guidance provided in the leakage section of ACM0009. In case leakage emissions in the baseline situation are higher than leakage emissions in the project situation, leakage emissions will be set to zero.

- - - - -

**History of the document**

Version	Date	Nature of revision
02	EB 54, Annex 11 28 May 2010	To include Greenfield project activities and to allow for non-element processes given that emission reductions are claimed for one output only.
01	EB 50, Annex 26 16 October 2009	Initial adoption.
<b>Decision Class:</b> Regulatory <b>Document Type:</b> Standard <b>Business Function:</b> Methodology		