

Indicative simplified baseline and monitoring methodologies
for selected small-scale CDM project activity categories

TYPE II - ENERGY EFFICIENCY IMPROVEMENT PROJECTS

Follow the link for [General guidance](#) / [Abbreviations](#) / [Full version of appendix B](#)

II.A. Supply side energy efficiency improvements – transmission and distribution

Technology/measure

32. This category comprises technologies or measures to improve the energy efficiency of an electricity or district heating transmission and distribution system by up to the equivalent of 15 GWh per year. Examples include upgrading the voltage on a transmission line, replacing a transformer, and increased insulation of the pipes in a district heating system. The technologies or measures may be applied to existing transmission or distribution systems or be part of an expansion of a transmission or distribution system.

Boundary

33. The project boundary is the physical, geographical boundary of the portion of the transmission and/or distribution system where the energy efficiency measures are implemented.

Baseline

34. For retrofit projects, the energy baseline is the technical losses of energy within the project boundary calculated as either:

- (a) The measured performance of the existing equipment;

OR

- (b) The performance of the existing equipment as determined using a standard selected in accordance with paragraphs 5 and 6 of the general guidance (section A) above.

35. In the case of new facilities the energy baseline is the technical losses of energy within the project boundary calculated using a performance standard for the equipment that would otherwise have been installed selected in accordance with paragraphs 5 and 6 of the general guidance (section A) above.

36. The emissions baseline is the energy baseline multiplied by an emission coefficient. If the energy displaced is electricity, the emissions coefficient (in kg CO₂equ/kWh) shall be calculated as described in paragraphs 28 and 29 for category I.D. For measures implemented to improve the efficiency of a district heating system, the emissions coefficient is that of the fossil fuel used by the system. IPCC default values for emission coefficients can be used.

Leakage

37. If the energy efficiency technology is equipment transferred from another activity, leakage calculation is required.

Indicative simplified baseline and monitoring methodologies
for selected small-scale CDM project activity categories

II.A. Supply side energy efficiency improvements – transmission and distribution (Cont.)

Monitoring

38. The energy performance of the project activity shall be the measured technical energy losses of the equipment installed unless such losses cannot be metered.⁶ If the technical energy losses cannot be determined from metered data, they shall be calculated using the test results when the installed equipment is commissioned, and if these are not available use the value determined in paragraphs 34 or 35 as appropriate.

⁶ When non-technical energy losses are small relative to technical energy losses, technical energy losses after implementation of the efficiency measures can be determined from metered data if available. The electricity or steam delivered to the portion of the system affected by the efficiency improvements as well as the electricity or steam received at the end of the portion of the system affected by the improvements are metered. If the portion of the transmission/distribution system affected by the energy efficiency improvements is not already separately metered, the reduced technical energy losses could be expressed as a percentage of the losses on a portion of the system that is already metered.

**Appendix B¹ of the simplified modalities and procedures for small-scale CDM project activities****INDICATIVE SIMPLIFIED BASELINE AND MONITORING METHODOLOGIES FOR
SELECTED SMALL-SCALE CDM PROJECT ACTIVITY CATEGORIES****A. General guidance**

1. This appendix contains indicative simplified baseline and monitoring methodologies for selected small-scale CDM project activity categories, including recommendations for determining the project boundary, leakage, baseline and monitoring.
2. In accordance with paragraphs 15 and 16 of the simplified modalities and procedures for small-scale CDM project activities (annex II to decision 21/CP.8 contained in document FCCC/CP/2002/7/Add.3), project participants involved in small-scale CDM project activities may propose changes to the simplified baseline and monitoring methodologies specified in this appendix or propose additional project categories for consideration by the Executive Board. Project participants willing to submit a new small-scale project activity category or revisions to a methodology shall make a request in writing to the Board providing information about the technology/activity and proposals on how a simplified baseline and monitoring methodology would be applied to this category. The Board may draw on expertise, as appropriate, in considering new project activity categories and/or revisions of and amendments to simplified methodologies. The Executive Board shall expeditiously, if possible at its next meeting, review the proposed methodology. Once approved, the Executive Board shall amend appendix B.
3. In accordance with paragraph 28 of the simplified modalities and procedures for small-scale CDM project activities, a simplified baseline and monitoring methodology listed in this appendix may be used for a small-scale CDM project activity if project participants are able to demonstrate to a designated operational entity that the project activity would otherwise not be implemented due to the existence of one or more barrier(s) listed in attachment A of this appendix.
4. The appendix reflects the following guidance regarding equipment performance, project boundary, biomass projects, leakage and use of Intergovernmental Panel on Climate Change (IPCC) default values for emission coefficients.
5. Equipment performance: To determine equipment performance, project participants shall use:
 - (a) The appropriate value specified in appendix B;
 - (b) If the value specified in sub-paragraph (a) is not available, the national standard for the performance of the equipment type (project participants shall identify the standard used);
 - (c) If the value specified in sub-paragraph (b) is not available, an international standard for the performance of the equipment type, such as International Organization for Standardization (ISO) and International Electrotechnical Commission (IEC) standards (project participants shall identify the standard used);

¹ This appendix has been developed in accordance with the simplified modalities and procedures for small-scale CDM project activities (contained in annex II to decision 21/CP.8, see document FCCC/CP/2002/7/Add.3) and it constitutes appendix B to that document. For the full text of the annex II to decision 21/CP.8 please see reference/documents section on UNFCCC CDM web site <http://unfccc.int/cdm>).

Appendix B of the simplified modalities and procedures for small-scale CDM project activities

Indicative simplified baseline and monitoring methodologies for selected small-scale CDM project activity categories

(d) If a value specified in sub-paragraph (c) is not available, the manufacturer's specifications provided that they are tested and certified by national or international certifiers.

6. Project participants have the option of using performance data from test results conducted by an independent entity for equipment installed under the project activity.

7. Project boundary: The project boundary shall be limited to the physical project activity. Project activities that displace energy supplied by external sources shall earn certified emission reductions (CERs) for the emission reductions associated with the reduced supply of energy by those external sources.

8. Biomass projects: In the case of project activities using biomass, leakage shall be considered.

9. In the cases where leakage is to be considered, it shall be considered only within the boundaries of non-Annex I Parties.

10. In the case of project participants using IPCC default values for emission coefficients, these shall be the most up-to-date values available in the "IPCC Good Practice and Guidance and Uncertainty Management in National Greenhouse Gas Inventories" and the "Revised 1996 IPCC Guidelines for National Greenhouse Gas Inventories". A link providing more updated information on IPCC default values for emission coefficients is available on the page for small-scale CDM project activities on the UNFCCC CDM web site: <http://unfccc.int/cdm/ssc.htm>.

Appendix B of the simplified modalities and procedures for small-scale CDM project activities

Indicative simplified baseline and monitoring methodologies for selected small-scale CDM project activity categories

Revision History of this document

This appendix has been developed in accordance with the simplified modalities and procedures for small-scale CDM project activities (contained in annex II to decision 21/CP.8, see document FCCC/CP/2002/7/Add.3) and it constitutes appendix B to that document. For the full text of the annex II to decision 21/CP.8 please see <http://unfccc.int/cdm.htm>. The first version was adopted by the Executive Board (EB) at its seventh meeting. This revision history was introduced with the second version of this document.

Version Number	Date	Description and reason of revision
02	2 December 2003	<i>- Incorporate amendments agreed by EB at its twelfth meeting - Layout changes in order to facilitate web publication and distribution: Each category of project types is presented in way that it may stand on its own with references to general guidance etc..</i>
03	30 June 2004	<i>- Incorporate amendments agreed by EB at its fourteenth meeting. Please see annex 2 of the report of EB14.</i>