

Indicative simplified baseline and monitoring methodologies
for selected small-scale CDM project activity categories

TYPE III - OTHER PROJECT ACTIVITIES

Project participants shall apply the general guidelines to SSC CDM methodologies and information on additionality (attachment A to Appendix B) provided at

<http://cdm.unfccc.int/methodologies/SSCmethodologies/approved.html> *mutatis mutandis*.

III.AK. Biodiesel production and use for transport applications

Technology/measure

1. This methodology comprises project activities for cultivation of oilseeds and/or sourcing of waste oil/fat¹ to be used in production of biodiesel² for use in transportation applications.^{3,4} **It also comprises project activities producing biodiesel as a by-product of oilseed processing.**
2. This methodology is only applicable if the final biodiesel blending proportion is a maximum of 20% by volume (B20). This is to ensure that technical performance characteristic of the blended biodiesel do not differ from those of petrodiesel. **This methodology is also applicable to higher blending proportions if the net calorific value of the produced biodiesel is at least equivalent to 95% of that of petrodiesel.**
3. Only biodiesel consumed in excess of mandatory regulations is eligible for the purpose of the project activity.⁵
4. This methodology is applicable under the following conditions:
 - (a) In the baseline situation the vehicles/transportation applications use diesel;
 - (b) Biodiesel or its blends are end-used in a captive fleet of vehicles/transportation applications;
 - (c) The petrodiesel, the biodiesel and the blended biodiesel comply with the national regulations (if existent) or with applicable international standards such as ASTM D6751, EN14214, or ANP42;
 - (d) Final users and the producer of the biodiesel and its blends are bound by a contract that states that the final consumers shall not claim emission reductions resulting from its consumption. The contract also enables the producer to monitor the consumption of biodiesel and its blends. Only the producer of the biodiesel can claim emission reductions under this methodology;
 - (e) The alcohol used for esterification is methanol from fossil fuel origin. Volumes of biodiesel produced with alcohols other than methanol (for example, ethanol) are

¹ Waste oil/fat is defined as a residue or waste stream of biogenic origin from restaurants, agro and food industry, slaughterhouses or related commercial sectors.

² Biodiesel is a diesel fuel consisting of long-chain alkyl (methyl, propyl or ethyl) esters which is produced by esterification of vegetable oils and/or waste oil/fat with alcohols from biogenic and/or fossil origin.

³ ~~Domestic water borne transport as defined by IPCC 2006, vol.2, chapter 3 can be considered as eligible.~~

⁴ **Domestic water borne transport as defined by IPCC 2006, vol.2, chapter 3 can be considered as eligible.**

⁵ Regulations that have been implemented since the adoption by the COP of the Modalities and Procedures of CDM (Decision 17/CP.7, 11 November 2001) need not to be taken into account.

Indicative simplified baseline and monitoring methodologies
for selected small-scale CDM project activity categories

III.AK. Biodiesel production and use for transport applications (cont)

not included in the quantity of biodiesel for which emission reductions are claimed;⁶

- (f) The export of biodiesel produced under this category is not allowed.

5. Measures are limited to those that result in emission reductions of less than or equal to 60 kt CO₂ equivalent annually.

6. The following conditions have to be met only if the feedstock for production of the biodiesel is vegetable oil produced from oil seeds cultivated in dedicated plantations:

- (a) The project activity does not lead to a shift of pre-project activities outside the project boundary i.e. the land under the proposed project activity can continue to provide at least the same amount of goods and services as in the absence of the project;
- (b) The plantations are established on a land:
 - (i) Which was at the start of the project implementation, classified as degraded or degrading as per the “Tool for the identification of degraded or degrading lands for consideration in implementing CDM A/R project activities”; or
 - (ii) Area that is included in the project boundary of one or several registered A/R CDM project activities.
- (c) Plantations established on the peatlands are not eligible even if qualifying under condition (b) above.

7. The following conditions have to be met only if the feedstock for production of the biodiesel is vegetable oil produced from oilseed crops, exclusively soybean, rapeseed, canola and/or sunflower, cultivated in non-dedicated cropland:

- (a) **The project activity does not lead to a shift of pre-project activities outside the project boundary, i.e. the land under the proposed project activity can continue to be used for agricultural production as in the absence of the project;**
- (b) **The project activity does not lead to an increase in the cultivation of oilseeds in the host country, as demonstrated by at least one of the following:**
 - (i) **The production in the host country of oilseeds used in the project activity is not limited by market demand (i.e., the size of the demand of oilseeds by the market where they are normally traded with little or no restrictions, is much higher than the capacity for their production in the host country);**

⁶ Only methanol from fossil fuel origin is included because the methodology does not provide procedures for estimating emissions associated with the use of other alcohols than methanol from fossil fuel origin. Project proponents are invited to propose procedures to estimate the emissions associated with the production of other alcohols that could be used for esterification, such as ethanol or methanol from renewable sources, as a revision to this methodology.

Indicative simplified baseline and monitoring methodologies
for selected small-scale CDM project activity categories

III.AK. Biodiesel production and use for transport applications (cont)

- (ii) **More than half of the production in the host country of oilseeds used in the project activity is exported to other countries;**
 - (c) **Deforestation is negligible in host country, which can be shown by demonstrating that any conversion of forest land in the host country, during the period of two years prior to the date of submission of the PDD for validation or for crediting period renewal, affected annually less than 0.1 per cent of the total area of forest land in the host country.**
 - (d) **The non-dedicated crops producing the oilseeds used by the project activity are established on lands that are identifiable; for which the land use and management at the project start date is known or can be inferred; and which have a history of being used for agriculture production for at least three years prior to the project start date.**
- 8. **The project activity producing biodiesel as a by-product from processing oilseed crops, exclusively soybean, rapeseed, canola and/or sunflower and applying to the following conditions, does not influence crop cultivation and therefore emissions from cultivation are assumed to be zero:**
 - (a) **The production in the host country of oilseeds used in the project activity is not limited by market demand (i.e., the size of the demand of oilseeds by the market where they are normally traded with little or no restrictions, is much higher than the capacity for their production in the host country);**
 - (b) **More than half of the production in the host country of oilseeds used in the project activity is exported to other countries;**
 - (c) **The processing of oilseeds in the project activity plant is mainly oriented to obtain oilseed meal and/or oil as main products, and biodiesel as a by-product. The biodiesel is considered as a by-product if the revenue from its sale, on an annual basis, is less than 30% of the total revenues obtained by the processing plant.**

Boundary

9. The project boundary is the geographical area of the oil seeds cultivation; itinerary for transportation of the feedstock sources⁷ processing of oil-seeds and biodiesel production, the sites where the waste water and solid waste are treated, the areas where -biodiesel is blended and sold to the final users. The vehicles/transportation applications of the final users where the biodiesel or blends thereof are consumed are also included in the project boundary.

⁷ Feedstock sources are the harvested parts of the plants from dedicated plantations **or non-dedicated cropland** that are transported from the fields to the facility for plant oil processing and/or biodiesel production. In case of waste oil/fat the feedstock sources are the activities where they are generated.

Indicative simplified baseline and monitoring methodologies
for selected small-scale CDM project activity categories

III.AK. Biodiesel production and use for transport applications (cont)

10. **In the case of non-dedicated crops, the boundaries of the geographical area where the oilseeds will be produced shall be broadly identified⁸. This area shall encompass the land units producing the oilseeds used by the project activity, in amounts exceeding those used by the project, as well as other agricultural products. These land units may also produce more than one crop of the same or different species per year. Monitoring of project emissions associated with the cultivation of lands for producing the oilseeds shall be conducted based on a sampling procedure described in paragraph 22.**

11. Baseline

12. Baseline emissions are calculated based on the amount of displaced petrodiesel determined as follows.

$$BE_y = BD_y \times NCV_{BD,y} \times EF_{CO_2,PD,y} \quad (1)$$

with

$$BD_y = \min[(P_{BD,y} - P_{BD,on-site,y} - P_{BD,other,y}), (f_{PJ,y} \times \int_{PD,y} \times C_{BBD,y} - P_{BD,other,y})] \quad (2)$$

Where:

BE_y	Baseline emissions during the year y (tCO ₂)
$NCV_{BD,y}$	Net calorific value of biodiesel produced for the year y
BD_y	Quantity of biodiesel eligible for crediting in year y (tonnes)
$P_{BD,y}$	Production of biodiesel in the project plant in year y (tonnes)
$P_{BD,on-site,y}$	Quantity of biodiesel consumed at the project biodiesel production plant in year y (tonnes)
$P_{BD,other,y}$	Quantity of biodiesel that is either produced with other alcohols than methanol from fossil origin or that is produced using other oil seeds or waste oil(s)/fat(s) than those eligible under this methodology according to the applicability conditions ⁹
$C_{BBD,y}$	Consumption of (blended) biodiesel from the project plant by the captive consumer(s) in year y (tonnes)
$f_{PJ,y}$	Fraction of blending in year y (volume ratio)
$EF_{CO_2,PD,y}$	Carbon dioxide emissions factor for petrodiesel (tCO ₂ /GJ)

⁸ The rationale follows the same approach as Reporting Method 1, described by IPCC good practice guidance for LULUCF for activities under Article 3, paragraphs 3 and 4, of the Kyoto Protocol

⁹ If in a particular year some amount of biodiesel produced has not been consumed and the excess stock is carried over to the next year then it can be added to the amount produced in the next year.

Indicative simplified baseline and monitoring methodologies
for selected small-scale CDM project activity categories

III.AK. Biodiesel production and use for transport applications (cont)

$f_{PD,y}$ 1.0 if pure petrodiesel is used for blending otherwise use the fraction of petrodiesel in the fuel used for blending (blending rate shall be established volume by volume)

13. BD_y is determined in equation 2 as the lowest value between the amounts calculated based on: (a) The production of biodiesel in year y ($P_{BD,y}$), and (b) The consumption of biodiesel by the captive consumers in year y ($C_{BD,y}$). In the case of blended biodiesel, the consumption of eligible quantity of biodiesel is calculated by the multiplying the consumption of eligible quantity of blended biodiesel by the blending fraction ($C_{BBD,y} * f_{PJ,y}$). In case the biodiesel produced by the project activity is blended with already blended biodiesel, then only the fraction of petrodiesel shall be considered ($f_{PD,y}$). Only those (blended) biodiesel quantity shall be considered as eligible for which the applicability conditions are fulfilled. Therefore, biodiesel quantity produced and consumed for the purpose of the project activity (self-consumption) are subtracted from the first amount, and quantity which do not fulfil the applicability criteria are subtracted from the amount of biodiesel in both cases.

14. Only biodiesel and blends thereof which are consumed by captive fleets and which is sold to the end users at filling stations and recorded by calibrated metering systems are included.

Project Activity Emissions

15. Project activity emissions are the emissions related to the cultivation of oil seeds and production and distribution of biodiesel (“field-to-tank” emissions). The emissions from the combustion of the renewable carbon content in biodiesel (“tank to wheel”) are carbon neutral and may be disregarded. The following sources of project emissions shall be considered:

- (a) Emissions associated with the cultivation of land to produce the oil seeds used for production of biodiesel/plant oil;
- (b) Emissions due to transportation of feedstock sources from their originating sites to the biodiesel production facility;¹⁰
- (c) Emissions from energy use for biodiesel production;
- (d) Emissions from fossil fuel carbon in the biodiesel due to the use of methanol from fossil origin in the trans-esterification process;
- (e) Where applicable CH_4 emissions due to stockpiling, land filling of solid waste generated by the project or from the waste water generated in the biodiesel production facility.

16. The project activity emissions of sources (a), (b) and (c) above will be allocated to the biodiesel produced from each oilseed type k and its co- and by-products, apportioning by market prices. For each oilseed type k the project emissions shall be calculated separately and then summed to determine the total project emissions in year y , as follows:

¹⁰ In case all the feedstock sources (crop cultivation areas) are situated within 50 km from the facility for biodiesel production the project emissions for transportation may be disregarded, however, in this case the long distance transportation of crude oil for petrodiesel production in the leakage section (paragraph 24) shall also be disregarded.

Indicative simplified baseline and monitoring methodologies
for selected small-scale CDM project activity categories

III.AK. Biodiesel production and use for transport applications (cont)

$$PE_y = \sum_k [FP_{BD,k,y} \times AF_{k,y} \times (PE_{CC,k,y} + PE_{TT,k,y} + PE_{PP,k,y})] + PE_{MeOH,y} + PE_{CH4,k,y} \quad (3)$$

Where:

PE_y	Project emissions in year y (tCO ₂ e)
$FP_{BD,k,y}$	Amount of biodiesel produced with plant oil type k that is produced by the project activity in year y (tonnes)
$AF_{k,y}$	Allocation factor for the production of biodiesel from oilseed type k in year y (fraction)
$PE_{CC,k,y}$	Emissions from cultivation of crops for oilseeds type k in year y (tCO ₂ e)
$PE_{TT,k,y}$	Emissions from transportation of feedstock sources of type k and/or biodiesel in year y (tCO ₂ e)
$PE_{PP,k,y}$	Emissions from biodiesel production using oilseeds type k in year y (tCO ₂ e)
$PE_{MeOH,y}$	Emissions from fossil fuel carbon in methanol used in the trans-esterification process in year y (tCO ₂ e)
$PE_{CH4,k,y}$	Where applicable project emissions of CH ₄ from solid waste and/or waste water in year y (tCO ₂ e)

17. The allocation factor is calculated using the amount of fuels, co-products and by-products obtained from the oilseed type k and respective market prices, as per the following equation:

$$AF_y = \frac{FP_{BD,k,y} \times MP_{BD,k,y}}{FP_{BD,k,y} \times MP_{BD,k,y} + M_{OM,k,y} \times MP_{OM,k,y} + M_{G,k,y} \times MP_{G,y}} \quad (4)$$

Where:

$FP_{BD,k,y}$	Amount of biodiesel from oilseed type k produced and consumed in the year y (tonnes)
$MP_{BD,k,y}$	Market price of biodiesel from oilseed type k in year y (\$/tonnes)
$M_{OM,k,y}$	Amount of oilseed meal (press-cake) obtained from oilseed type k in year y (tonnes)
$MP_{OM,k,y}$	Market price of oilseed meal (press-cake) obtained from oilseed type k in year y (\$/tonnes)
$M_{G,k,y}$	Amount of glycerin associated with the production of biodiesel from oilseed type k in year y (tonnes)
$MP_{G,y}$	Market price of glycerin in year y (\$/tonnes)

If any other co-products or by-products from oilseed crop type k are sold in the market, they may be included in the denominator of the above equation accordingly.

Indicative simplified baseline and monitoring methodologies
for selected small-scale CDM project activity categories

III.AK. Biodiesel production and use for transport applications (cont)

Project emissions associated with the cultivation of lands to produce oil seeds ($PE_{BC,y}$)

18. This step calculates emissions associated with the cultivation of lands to produce the oil seeds used for biodiesel production.

19. If the oil seeds are sourced from a plantation area that is registered as one or several A/R CDM project activities, these emissions are not accounted as project emissions under this methodology.

Project participants may choose among two options to calculate this emission source:

- Option A provides a simplified approach, using conservative default values for the emissions associated with the cultivation of lands, taking into account different geographical regions where the crop is grown. This approach can only be used for oil seeds from palm or jatropha; **in dedicated plantations;**
- Option B calculates the emissions based on actual data from the cultivation process and is more accurate than option A but requires additional data collection efforts.

Option A: Use of a default emission factor

$$PE_{CC,k,y} = A_{k,y} \times EF_{k,y} \quad (5)$$

Where:

$A_{k,y}$	Total area in which oil seed type k is cultivated for use in the project plant in year y (ha)
$EF_{k,y}$	Default emission factor for the GHG emissions associated with the cultivation of land to produce oil seed type s (tCO ₂ e/ha). See table III.AK.1 below for available values

Table III.AK.1: Conservative default emission factors for the GHG emissions associated with the cultivation of land to produce oil seeds

Crop	Climate Zone	EF _{s,v} (tCO ₂ e/ha)
Palm	Tropical Moist	1.87
Palm	Tropical Wet	1.87
Jatropha	Tropical Moist	1.76
Jatropha	Tropical Dry	2.52

Option B: Use of project specific data

20. Project emissions associated with the cultivation of land shall be determined as per the relevant procedures of ACM0017.

21. **If the project activity is located next to a silo plant, which was operating for at least three years prior to the starting date of the project activity and consumes less than 30% of the oilseed flow of the silo plant on a yearly basis, and applicability conditions listed in**

Indicative simplified baseline and monitoring methodologies
for selected small-scale CDM project activity categories

III.AK. Biodiesel production and use for transport applications (cont)

paragraph 7 are applicable, it is assumed that the project activity does not influence crops production¹¹ and therefore emissions are assumed zero.

22. In the case of non-dedicated cropland, the data needed for application of procedures of ACM0017 shall be obtained through a sampling procedure described in steps 1 to 6 below. Due to the use of a sampling approach, emissions associated with the cultivation of land shall be estimated on a per unit mass of oilseeds basis. In the case that more than one oilseed type or species is used, emissions shall be estimated separately for each.

Step 1. Identification of individual units of land

Land units from which oilseeds used by the project activity originate shall be identified and recorded. In the case that the project activity gets the oilseeds from a silo or any other storage place where oilseeds not used by the project activity are also stored, making it impossible to trace the origin of the grains used by the project, project developers shall identify and record at least 90 per cent of the land units where all oilseeds stored there were produced.

Step 2. Random selection of a sample of units of land from which data is collected

Select randomly a sample of units of land according to guideline “General Guidelines for Sampling and Surveys for SSC CDM project activities”¹². Record the details of the selected land units.

Step 3. Assess the eligibility of land units selected

Assess each land unit by its compliance with eligibility conditions described in paragraph 7(d). Collect information on land use and management at the project start date, and evidence that the land had been under agricultural use for at least three years before project start date. Identify any non-eligible land units.

Step 4. Allocation of CO₂ emissions from changes in soil carbon stocks (PE_{CO₂,soil,y}) to products

In cases where there is more than one product obtained in a unit of land during the period of one year prior to the date of harvest of the oilseed, the estimated value of PE_{CO₂,soil,y} for that unit of land shall be apportioned to each product, according to the following:

$$AF_{C,j,y} = \frac{\sum_k CC_{j,k,y} \times MP_{CC,k,y}}{\sum_k TC_{j,k,y} \times MP_{TC,k,y}} \quad (6)$$

Where:

AF_{C,j,y} Allocation factor for emissions from changes in soil carbon stocks for each land unit j in year y

¹¹ The rationale is that under the listed applicability conditions and in this particular case, the project activity does not influence the oilseed cultivation, but consumes a small fraction of an existing oilseed flow that is mainly exported.

¹² EB50 – annex 30

Indicative simplified baseline and monitoring methodologies
for selected small-scale CDM project activity categories

III.AK. Biodiesel production and use for transport applications (cont)

$MP_{CC,k,y}$	Market price of oilseed type k , consumed by the project activity, in year y (\$/tonnes)
$CC_{j,k,y}$	Total amount of oilseed type k , consumed by the project activity, cultivated in land unit j , in year y
$MP_{TC,k,y}$	Market price of crops type k cultivated in year y (\$/tonnes)
$TC_{j,k,y}$	Total amount of crops cultivated in land unit j in year y

Step 5. Estimation of emissions per unit mass of oilseed

The emissions associated with the cultivation of land shall be estimated on an oilseed-mass unit basis, for each type of oilseed used by the project activity. Emissions from oilseed cultivation shall be estimated as the average emissions of all land units weighted by their area.

Step 6. Treatment of any non-eligible land units

In the cases that the assessment made in step 3 yields non-eligible lands, the fraction of oilseeds originating in these areas over the total oilseeds used by the project activity (or from all oilseeds stored in silos from which the project activity gets the supply) shall be not considered for estimating the project activity's emission reductions.

23. The project emissions from transportation of feedstock and biodiesel is calculated as follows:

$$PE_{TT,k,y} = (Q_{k,y} / CT_y) \times DAF_{k,y} \times EF_{CO_2} \quad (7)$$

Where:

$Q_{k,y}$	Quantity of feedstock from oilseed type k transported from the cultivation area to the processing/producing facility or biodiesel transported from production plant to blending site or site of its consumption in the year y (tonnes)
CT_y	Average truck capacity for transportation (tonnes/truck)
$DAF_{k,y}$	Average distance for feedstock transportation for oilseed type k (km/truck)
EF_{CO_2}	CO ₂ emission factor from fuel use due to transportation (kgCO ₂ /km, IPCC default values or local values may be used)

24. Project emissions from energy use for processing (e.g. pressing and filtering, transesterification, degumming, neutralization) are determined as follows:

$$PE_{PP,k,y} = EC_{PP,k,y} \times EF_{CO_2,ELEC} + \sum_i (FC_{i,PP,k,y} \times NCV_i \times EF_{CO_2,i}) \quad (8)$$

Indicative simplified baseline and monitoring methodologies
for selected small-scale CDM project activity categories

III.AK. Biodiesel production and use for transport applications (cont)

Where:

$EC_{PP,k,y}$	Electricity consumption in biodiesel production for crop k or for processing of the waste oil/fat in year y (MWh)
$EF_{CO_2,ELEC}$	Emissions factor for grid electricity supplied to the project facility using the calculation methods of AMS-I.D (tCO ₂ e/MWh)
$FC_{i,PP,k,y}$	Consumption of fossil fuel type i for plant oil processing or biodiesel production from crop k or from waste oil/fat in year y (tonnes)
NCV_i	Net calorific value of fossil fuel i (GJ/tonnes)
$EF_{CO_2,i}$	Emissions factor of fossil fuel i (tCO ₂ /GJ fuel)

25. Project emissions from fossil fuel carbon in the biodiesel due to the use of methanol from fossil origin in the esterification process are estimated as follows:

$$PE_{MeOH,y} = MC_{MeOH,y} \times EF_{C,MeOH} \times \frac{44}{12} \quad (9)$$

Where:

$PE_{MeOH,y}$	Project emissions from fossil carbon in the biodiesel due to esterification with methanol of fossil origin in year y (tCO ₂ e)
$MC_{MeOH,y}$	Quantity of methanol consumed in the biodiesel plant, including spills and evaporations in year y (tonnes)
$EF_{C,MeOH}$	Carbon emission factor of methanol, based on molecular weight (tC/tMeOH) (= 12/32)
$\frac{44}{12}$	Molecular weight ratio to convert tonnes of carbon into tonnes of CO ₂ (tCO ₂ /tC)

26. Project emission of CH₄ from solid waste disposal and/or wastewater treatment is calculated as per provisions in AMS-III.G (landfill), AMS-III.F (composting) or AMS-III.H (waste water treatment).

Leakage

27. If it is demonstrated that the use of the waste oil/fat by the project activity does not result in increased fossil consumption elsewhere the leakage from the displacement of existing uses of waste oil/fat is to be neglected, otherwise the leakage should be considered as per the relevant provisions of ACM0017 and its equations 12, 13 and 14.

28. Leakage effects due to the upstream emissions for the methanol production may be disregarded, if the leakage due to the avoided production of petrodiesel (including production of crude oil and refining of crude oil) is also disregarded. Otherwise, the leakage emissions due to the production of methanol used in the esterification process shall be calculated as per the relevant equation 11 of ACM0017.

Indicative simplified baseline and monitoring methodologies
for selected small-scale CDM project activity categories

III.AK. Biodiesel production and use for transport applications (cont)

29. The substitution of plant oil for petrodiesel reduces indirect (“upstream”) emissions associated with the production of petrodiesel and is treated as negative leakage¹³ and can be calculated as per the relevant sections of ACM0017 and its equations 16, 17 and 18.

Emission Reduction

30. The emission reductions achieved by the project activity shall be calculated as the difference between the baseline emissions and the sum of the project emissions and leakage.

$$ER_y = BE_y - PE_y - LE_y - LE_{WOF,y} - LE_{MEOH,y} + LE_{PD,y} \quad (10)$$

Where:

ER_y	Emission reductions in the year y (tCO ₂ e)
LE_y	Leakage due to equipment transfer in year y (tCO ₂ e)
$LE_{PD,y}$	Leakage related to the avoided production of petrodiesel (tCO ₂ /yr)
$LE_{MEOH,y}$	Leakage emissions associated with production of methanol used in biodiesel production in year y (tCO ₂)
$LE_{WOF,y}$	Leakage emissions from displacement of existing utilization of waste oil/fat in year y (tCO ₂)

Monitoring

31. Relevant parameters shall be monitored as indicated in the Table III.AK.2 below. The applicable requirements specified in the “General guidelines to SSC Methodologies” (e.g. calibration requirements, sampling requirements) are also an integral part of the monitoring guidelines specified below and therefore shall be referred by the project participants.

¹³ Emission reduction from reducing international bunker fuel consumption is not eligible under CDM as per EB 25 report, paragraph 58.

Indicative simplified baseline and monitoring methodologies
for selected small-scale CDM project activity categories

III.AK. Biodiesel production and use for transport applications (cont)

Table III.AK.2

No	Parameter	Description	Unit	Monitoring/ recording Frequency	Measurement Methods and Procedures
1	$A_{k,y}$	Total area in which oil seed type k is cultivated for use in the project plant in year y -, in case of dedicated plantations.	ha	Annually	Measured or calculated (e.g. using maps). Measurements results shall be consistent with yield of the cultivation
2	$P_{BD,y}$	Production of biodiesel in the project plant in year y	tonnes	Continuously or in batches	Measurements are undertaken using calibrated meters. Measurement results shall be cross checked with records for consumption and sales (e.g. invoices/receipts)
3	$P_{BD,on-site,y}$	Quantity of biodiesel that is either produced with other alcohols than methanol from fossil origin or that is produced using other oil seeds or waste oil(s)/fat(s) than those eligible under this methodology according to the applicability conditions	tonnes	Continuously or in batches	Measurements are undertaken using calibrated meters at production site
4	$P_{BD,on-site,y}$	Quantity of biodiesel consumed at the project biodiesel production plant and/or the oil production plant(s) in year y	tonnes	Continuously or in batches	Measurements are undertaken using calibrated meters at production site

Indicative simplified baseline and monitoring methodologies
for selected small-scale CDM project activity categories

III.AK. Biodiesel production and use for transport applications (cont)

No	Parameter	Description	Unit	Monitoring/ recording Frequency	Measurement Methods and Procedures
5	$C_{BBD,y}$	Consumption of (blended) biodiesel from the project plant by the captive consumer(s) in year y	tonnes	Continuously or in batches	Measurements are undertaken using calibrated meters at fuelling stations. Measured with calibrated metering system at fuelling stations. Measurement results shall be cross checked with records for sales (e.g. invoices/receipts)
6	$NCV_{BD,y}$	Net calorific value of biodiesel produced in year y	GJ/tonnes	Annually	Measured according to relevant national/ international standards Analysis has to be carried out by accredited laboratory
7	$f_{PJ,y}$	Fraction of blending in year y (ratio)	%	Continuously	Measured volumes or flows by calibrated meters at blending stations. To be determined as per ACM0017
8	$f_{PD,y}$	Fraction of petrodiesel in the fuel used for blending	%	Continuously or in batches	Data from the supplier of the fuel used for blending
9	$FP_{BD,k,y}$	Amount of biodiesel from oilseed type k produced and consumed in the year y (tonnes)	tonnes	Continuously or in batches	Measurements are undertaken using calibrated meters at fuelling stations. Measurement results shall be cross checked with records for consumption and sales (e.g. invoices/receipts)
10	$M_{OM,k,y}$	Amount of oilseed meal (press-cake) obtained from oilseed type k in year y (tonnes)	tonnes	Continuously or in batches	Measurements are undertaken at production site. Measurement results shall be cross checked with records for consumption and sales (e.g. invoices/receipts)

Indicative simplified baseline and monitoring methodologies
for selected small-scale CDM project activity categories

III.AK. Biodiesel production and use for transport applications (cont)

No	Parameter	Description	Unit	Monitoring/ recording Frequency	Measurement Methods and Procedures
11	$M_{G,k,y}$	Amount of glycerin associated with the production of biodiesel from oilseed type k in year y (tonnes)	tonnes	Continuously or in batches	Measurements are undertaken at production site. Measurement results shall be cross checked with records for consumption and sales (e.g. invoices/receipts)
12	$Q_{k,y}$	Quantity of feedstock from oilseed type k transported from the cultivation area to the processing/producing facility and biodiesel from production plant to blending site or site of its consumption in the year y (tonnes)	tonnes	Continuously or in batches	Measurements are undertaken using calibrated mass or volumetric meters at production site for every transported material (e.g. oil seeds, plant oil, biodiesel)
13	CT_y	Average truck capacity for transportation (tonnes/truck)	tonnes	Annually	Records of truck operator, plant records, vehicle manufacturer information
14	$DAF_{k,y}$	Average distance for feedstock transportation for oilseed type k (km/truck)	km	Annually	Measurements are undertaken using vehicles odometer readings. The consistency of distance records provided by truck operators shall be cross-checked with other information sources (e.g. maps)
15	$EF_{CO_2,E,LEC}$	CO ₂ emission factor for grid electricity supplied to the project plant in year y	tCO ₂ e/ kWh	Annually	Grid emission factor shall be determined following the provisions of AMS-I.D
16	$EF_{CO_2,i}$	CO ₂ emission factor of fossil fuel type i	tCO ₂ e/ GJ	Annually	As per the “Tool to calculate project or leakage CO ₂ emissions from fossil fuel combustion”

Indicative simplified baseline and monitoring methodologies
for selected small-scale CDM project activity categories

III.AK. Biodiesel production and use for transport applications (cont)

No	Parameter	Description	Unit	Monitoring/ recording Frequency	Measurement Methods and Procedures
17	EC _{PP,k,y}	Electricity consumption in biodiesel production for crop <i>k</i> or for processing of the waste oil/fat in year <i>y</i>	MWh	As per the “Tool to calculate baseline, project and/or leakage emissions from electricity consumption”	As per the “Tool to calculate baseline, project and/or leakage emissions from electricity consumption”
18	NCV _i	Net calorific value of fossil fuel type <i>i</i>	GJ/mas s or volume unit	Annually	As per the “Tool to calculate project or leakage CO ₂ emissions from fossil fuel combustion”
19	FC _{PP,i,k,y}	Consumption of fossil fuel type <i>i</i> for biodiesel production from crop <i>k</i> or from waste oil/fat in year <i>y</i> (tonnes)	Mass or volume unit	As per the “Tool to calculate project or leakage CO ₂ emissions from fossil fuel combustion”	As per the “Tool to calculate project or leakage CO ₂ emissions from fossil fuel combustion”
20	NCV _{PD}	Net calorific value of diesel	GJ/ton		2006 IPCC Guidelines on National GHG Inventories
21	MC _{MeO}	Mass of MEOH consumed in the biodiesel plant, including spills and evaporation, in year <i>y</i>	tonnes	Continuously or in batches	Measured continuously by calibrated equipment at the project site. Cross-checked with purchase data and adjusted for stock changes when deemed necessary
22	TA _{k,C}	Total area of the defined region, composed of land units in which oil seed type <i>k</i> is cultivated for use in the project plant in year <i>y</i>, in case of non-dedicated plantations.	ha	Annually	Measured or calculated (e.g. using maps). Measurements results shall be consistent with yield of the cultivation
23	CC _{i,k,y}	Total amount of	tonnes	Annually	Measured or calculated (e.g.

Indicative simplified baseline and monitoring methodologies
for selected small-scale CDM project activity categories

III.AK. Biodiesel production and use for transport applications (cont)

No	Parameter	Description	Unit	Monitoring/ recording Frequency	Measurement Methods and Procedures
		oilseed type k , consumed by the project activity, cultivated in land unit j , in year y			using maps). Measurements results shall be consistent with yield of the cultivation
24	$MP_{CC,k}$	Market price of oilseed type k , consumed by the project activity, in year y (\$/tonnes)	\$/tonne	Annually	Official market price
25	$TC_{j,k,y}$	Total amount of crops cultivated in land unit j in year y	tonnes	Annually	Measured or calculated (e.g. using maps). Measurements results shall be consistent with yield of the cultivation
26	$MP_{TC,k}$	Market price of crops type k cultivated in year y (\$/tonnes)	\$/tonne	Annually	Official market price
27	$M_{OIL,k}$	Amount of oil obtained from oilseed type k in year y (tonnes) and not applied to biodiesel production	tonnes	Continuously or in batches	Measurements are undertaken at production site. Measurement results shall be cross checked with records for consumption and sales (e.g. invoices/receipts) and oil content.
28	$QP_{k,y}$	Amount of oilseed type k produced in the host country in year y	tonnes	Annually	Official Data Parameter applicable in cases specified in paragraphs 7 and 8.
29	$QE_{k,y}$	Amount of oilseed type k exported by the host country in year y	tonnes	Annually	Official Data Parameter applicable in cases specified in paragraphs 7 and 8.
30	$R_{P,y}$	Annual revenue obtained from co-product and by-product P in the year y	\$	Annually	Measurement results shall result from sales records (e.g. invoices/receipts).

Indicative simplified baseline and monitoring methodologies
for selected small-scale CDM project activity categories

III.AK. Biodiesel production and use for transport applications (cont)

Project activity under a programme of activities

32. The methodology is applicable to a programme of activities.

- - - - -

History of the document

Version	Date	Nature of revision
01	EB 55 , Annex 30 30 July 2010	Initial adoption.
Decision Class: Regulatory Document Type: Standard Business Function: Methodology		